

SECTION I

CHASSIS SPECIFICATIONS

TYPE A1 (19-29 Capacity)

TYPE A2 (30-47 Capacity)

DUAL REAR WHEEL

CUTAWAY CHASSIS

**BASIC MINIMUM SPECIFICATIONS
FOR TYPE A GASOLINE AND DIESEL SCHOOL BUS CHASSIS
FOR MOUNTING TYPE A1 (19-29 capacity) and A2 (30-47 capacity)
SCHOOL BUS BODIES**

1. **ALTERNATOR**

Type A1, 120 amp minimum rating, 50-amp minimum output at manufacturer's recommended engine idle speed; dual belts or poly-vee type belt, maximum ratio 2.5 to 1; sealed ball or roller bearings, meeting National School Transportation Specifications and Procedures.

All Type A2 chassis shall be equipped with an alternator producing at least 160 amperes current output hot rated.

2. **BATTERY (IES)**

Total of 1,200 CCA minimum at 0°F, 12 volt for all Type A1 buses. Total of 1,750 CCA minimum at 0°F, 12 volt; temporary frame mount location for all Type A2 buses.

3. **BRAKE, PARKING**

On hydraulic brake model A2 chassis an Orschelin-type control, or approved equal, mounted for easy access by the driver is required. On air brake models a dash-mounted control valve to spring-set the parking brake on the rear wheels is required. On Type A1 chassis, manufacturer's standard is acceptable.

4. **BRAKES, SERVICE**

- a. Hydraulic Brakes: Hydraulic brake models shall have power assist and shall meet National School Transportation Specifications and Procedures, Revised 2005, and all applicable Federal Motor Vehicle Safety Standards. Brake lining material shall not contain asbestos. Type A1 and A2 buses equipped with hydraulic brakes shall be equipped with manufacturer's standard antilock brake system.
- b. Air Brakes: Air brake models shall meet National School Transportation Specifications and Procedures, Revised 2005, and all applicable Federal Motor Vehicle Safety Standards. Air brake models shall be equipped with a desiccant dryer with an automatic purge and drain cycle and a heating element. Drum-type air brakes on the rear axle of 47 capacity chassis must have minimum 7 inch wide linings. Drum-type air brake lining thickness must be a minimum (except taper) of 3/4 inch on the rear axle and 3/8 inch on the front axle for all capacity chassis. All drum-type air brakes shall be cam-actuated. All slack adjusters (as equipped) shall be automatic adjustment type. All air brake models (drum, disc-drum, or air disc) must be equipped with spring-set parking brakes on the rear wheels. All brake drums shall be outboard mounted; i.e., drums shall be removable without removal of the axle hub. Brake lining material shall not contain asbestos. A minimum 12 CFM, engine oil-fed air compressor is required on all air brake models. Clean air to the air compressor shall be supplied from "clean" side of engine air cleaner or air system. Compressor shall not be equipped with separate, compressor-mounted air filter. Air brake system design shall provide for anti-compounding of service and emergency brakes, spring brake modulation upon application of front service brakes in event of loss of air pressure to rear service brakes, and brake S-cam rotation in same direction as forward wheel rotation. The rear axle of all buses with air brakes shall be equipped with grease guards to divert excessive oil or grease leaks away from brake linings in the event of a rear wheel seal leak or the bidder must provide warranty of rear axle seals and brake components as noted in the Chassis Warranties section. Buses equipped with air brakes shall be equipped with a four channel Antilock Braking System with independent controls for each wheel position.

5. **BUMPER, FRONT**

Type A1

Channel design, minimum 6 inches, and full width.

Type A2

Must be black, full-width channel type, minimum 8 inches, of sufficient structural and mounting strength to ensure that front of vehicle may be lifted by means of an air bumper-type jack, without permanent deformation of the bumper, brackets, or chassis frame rail(s).

6. **BUMPER, REAR**

Type A1 and A2

Supplied by body manufacturer. See Section III.

7. **COMPONENT ACCESSORY DRIVE**

Components such as alternator, air compressor, and power steering shall deliver to rated requirements without drive slippage at maximum load.

8. **DIFFERENTIAL RATIO**

Shall be compatible with engine and provide for 60 MPH in highest gear. Also see **ENGINE PERFORMANCE, Page I-5 and Page II-5.**

9. **DRIVESHAFT GUARDS AND SHIELDS**

Required. At least one per driveshaft section.

10. **ENGINE EQUIPMENT**

- a. Dry type air cleaner: Required. An air filter restriction indicator is required on diesel engines in Type A2 buses.
- b. Oil filter(s): Engine shall be equipped with full-flow, spin-on, or cartridge-type oil filter(s), with filter header(s) mounted directly to engine.
- c. Engine coolant recovery or deaeration system: Required on all chassis. Type A2 diesel engines must include means for visually checking coolant level without removing deaeration tank cap or releasing pressure from cooling system.
- d. Warning system consisting of light and buzzer: Required on diesel powered Type A2 chassis to notify driver of low engine oil pressure and/or coolant overheating.
- e. Fuel Filtration / Water Separation: Required on all Type A2 diesel engines. The system shall remove all contamination capable of adversely affecting the fuel system from the fuel prior to entry into the engine. The system shall be designed to remove contaminants normally found in Florida, including dirt, water, and algae. The system shall be designed with the capacity necessary to last 15,000 miles or more between filter changes. Manufacturers that do not meet this requirement shall be required to provide fuel filters free of charge to districts until they have retrofitted systems that will meet this requirement on all units produced with an inadequate system. Engines damaged due to inadequate filtration shall be repaired by the manufacturer at no cost to the district. System shall have a clear sight bowl, or be equipped with a water-in-fuel light to notify technicians of the presence of water. System must provide a valve for draining trapped water from the system.

- f. Engine oil pressure gauge: Required. It shall provide accurate, easily discernible readings across the entire operating range from hot idle to full oil pressure. Gauge on engines with idle oil pressure that under normal conditions is low shall provide a clear distinction between no oil pressure and engine idle oil pressure. Gauge shall be directly visible to driver in normal seated position and shall not be mounted near center of dash where body door control or associated hardware could block its visibility.
- g. Governor: Required on all diesel engines. Shall permit controlled engine RPM up to manufacturer's recommended maximum for engine used.
- h. Ignition switch: Controls running and shutdown of engine. Running of engine shall require electrical current provided by the ignition switch in the "start" and "run" positions. Engine shutdown shall result when current is cut off (ignition switch "off" position).
- i. Engine throttle control: The force required to operate the throttle shall not exceed 16 pounds through the full range of accelerator pedal travel.
- j. Radiator and other engine coolant hoses supplied by chassis manufacturer (not including heater hoses) shall be constructed of silicone rubber or hoses with EPDM covering and aramid fiber reinforcement meeting or exceeding SAEJ20R EC Class D-1. Silicone hose, if used, shall require the use of stainless steel shoe-type hose clamps or constant-torque clamps. Hoses shall have markings, coloring, or other visible means of distinguishing this hose from the standard hoses.

11. **ENGINE PERFORMANCE REQUIREMENTS FOR TYPE A2 BUSES**

- a. Each bus shall be furnished with a power train that meets or exceeds the following minimum criteria when tested at the GVWR required for a given bus capacity, and with all accessories (including air conditioner compressor(s), if equipped) on and operating:
 - (1) Startability of 20 percent.
 - (2) Gradeability of 5 percent at 25 miles per hour.
 - (3) Gradeability of 1.5 percent at 50 miles per hour.
 - (4) Top speed of 60 miles per hour minimum.
- b. Power train shall provide acceleration performance as specified in (3) below. Test conditions are as follows:
 - (1) As generated by an Allison SCAAN with the following parameters used:
 - (a) Vocation file number 2610.
 - (b) At gross vehicle weight for the specific bus size as listed in this manual.
 - (c) Tire size must be tire size listed herein for the specific size of bus.
 - (d) 6 total tires in contact with the road.
 - (e) Total driveline reduction factor used for the SCAAN must equal the reduction supplied in the completed chassis.
 - (f) Driveline efficiency 96.13 percent.
 - (g) Road surface factor 1.200.
 - (h) Vehicle height and width 10 feet X 8 feet.
 - (i) Air resistance coefficient 0.55.

- (2) As measured with the actual completed vehicle (i.e., with body installed, unloaded except for the driver and one passenger). The vehicle shall be in drive, engine at idle, service brakes applied, emergency brakes released, and all accessories on and operating. Measurement of acceleration time shall begin at the moment the throttle is applied (the throttle is to be immediately and rapidly depressed to full throttle).

NOTE: Chassis manufacturer should use the heaviest chassis/body combination meeting these specifications for the specific size bus to determine required power train components. This test is an on-road test and will be performed using the heaviest available chassis/body, depending on body(ies) supplied. At the discretion of the Department, unanticipated factors or variations in test conditions affecting performance test results that are beyond the control of the chassis manufacturer may be taken into account.

- (3) Maximum acceleration time (from zero mph), under conditions specified above, shall be as follows (measured in seconds):

TEST METHOD	0-10 MPH	0-20 MPH	0-30 MPH	0-40 MPH	0-50 MPH
1) SCAAN	2.9	8.1	16.8	30.1	53.8
2) ACTUAL	3.4	6.2	12.0	20.0	32.2

- (4) Manufacturers may offer additional engine configurations and horsepower ratings that exceed these requirements as optional equipment.

12. **EXHAUST SYSTEM**

Type A1

Shall be corrosion resistant and exhaust shall exit behind rear wheels and left of the left frame rail. Exception: Dual exhaust acceptable on Type A1 diesel chassis.

Type A2

Corrosion resistant muffler; exhaust pipe must extend 5 inches beyond chassis frame on stripped chassis. Tailpipe must exit to the left of left frame rail and behind rear wheels. Chassis manufacturer shall ensure that exhaust design allows exit location left of left frame rail to be maintained after any modifications to frame length by chassis or body manufacturer. Manufacturers must ensure that exhaust temperature exiting the tailpipe during any normal loading or unloading activity with the engine running will not produce first, second, or third degree burns on students or other individuals present. The bus shall not automatically regenerate the diesel particulate filter while the bus is stationary.

13. **FRAME SIDE MEMBERS**

One-piece construction.

14. **FRONT AXLE WHEEL SEALS**

All Type A2 buses shall have oil-lubricated front axles and seals.

15. **FUEL TANK**

Spout located for ease in servicing. Gauge shall be compatible with tank capacity and shall meet requirements of Federal Motor Vehicle Safety Standard 301. See Chassis Specifications Chart in this Section for minimum tank capacities by size.

16. **HEADLIGHTS**

1. Must meet SAE and Federal Standards and shall use a quartz halogen bulb. All units must be equipped with Full-Time Lights (FTL) meeting the following requirements:
 - a. With the ignition switch off, the headlights will operate normally and the FTL system will not operate.
 - b. With the ignition switch on or in the accessory position, and with the engine not running, the FTL shall not operate.
 - c. With the ignition switch on and the engine running and with the headlight switch off, the FTL system must operate, providing low beam headlights, tail, clearance, and ID lights. This activation may be accomplished by any reasonable means including the use of the park brake system.
 - d. In all cases the headlight switch must override the FTL system when in the “on” position.
 - e. This system shall include a buzzer that activates if the headlight system is on with the key switch in the “off” position.

17. **HORNS**

120 decibels (see National School Transportation Specifications & Procedures and FMVSS).

18. **IGNITION SYSTEM**

All Type A2 ignition systems shall be keyed alike. All buses of like chassis manufacturer shall have one key regardless of type supplied to the State of Florida.

19. **INSULATION**

Type A2 chassis shall include heat and noise insulation inside the bus covering the dash panel (fire wall) area to as great an extent as possible and at least down to the point that the body floor connects to the fire wall, including engine cover (doghouse), which may be insulated on the interior or exterior.

20. **LINE-SETT TICKET**

Manufacturer shall include with delivery of vehicle a line-sett ticket to accurately reflect the following: a) all chassis components; b) GAWR of both front and rear axles; and c) GVWR.

21. **ODOMETER**

Type A1: Accrued mileage, 6 digits, including tenths of miles (99,999.9 mile odometer).

Type A2: Accrued mileage, 7 digits, including tenths of miles (999,999.9 mile odometer).

22. **PAINT AND FINISH**

Prior to the application of the finish coats to chassis hood, fenders, and cowl, all surfaces shall be cleaned of grease, foreign matter, excess caulking and sealing material, and treated as per paint manufacturer's recommendation for proper paint adhesion. School bus yellow paint shall meet SBMTC-008 for color and shall have a finished gloss rating of at least 85 at 60°F and a distinctness of image rating of an average of at least 50 measured using the same method specified for gloss under WARRANTIES. Paint shall be applied for a total dry thickness of at least 1.8 mils over all painted surfaces. Trim, lettering, and bumper shall be black except that bumper may be striped with reflective material in accordance with National School Transportation Specifications and Procedures or these specifications. Rims for all Type A1 buses shall be manufacturer's standard. Rims for all Type A2 buses with hub-piloted wheels shall be powder-coated, National School Bus Yellow at the rim manufacturer. All Type A2 stud-piloted rims shall be painted black. Lead-free paint shall be used on all interior and exterior surfaces of the body and chassis. Also see **WARRANTIES, page 12** for warranty requirements.

23. **SHOCK ABSORBERS**

Front and rear, double-acting; adequate size for axle load.

24. **SPRINGS, FRONT**

Type A2: Double-wrap stationary end (see **Chassis Specifications Chart, page I-9**).

25. **SPRINGS, REAR**

Type A2: Progressive type (see **Chassis Specifications Chart, page I-9**).

26. **STEERING**

Shall have factory installed power steering, integral type. A factory installed tilt steering wheel/column is required.

27. **TIRES AND RIMS**

Chassis shall be equipped with radial tubeless tires. Type A1 buses shall have dual rear wheels (see **Chassis Specifications Chart, page I-9**). Type A2 buses shall use hub-piloted disc wheels. Tires and rims shall conform to current standards of Tire and Rim Association.

28. **TRANSMISSION, AUTOMATIC**

Automatic transmission required on all chassis. Heavy-duty, minimum 4-speed forward on all units. On Type A2, 30 capacity and larger, Allison 1000 or 2000 or approved equal. An external filter in the transmission oil cooler return line is required on Allison 1000 and 2000 equipped units.

29. **TURN SIGNALS**

Dash indicator light, self-canceling switch with lead wires on steering column for body manufacturer's attachment.

30. **VOLTAGE CONTROL**

Regulator: solid state components (transistorized) readily accessible for service. Voltmeter required: graduated scale.

31. **WARRANTIES**

See required chassis warranties, page 12.

32. **WIRING HARNESS**

100 amps load and complete wiring for tail and stop lights; color-coded circuits. Fuse box door, if equipped, shall have a positive latch.

Chassis Specifications Chart Type A1 and A2 Buses

<u>Maximum Design (Passenger) Capacity</u>		<u>19</u>	<u>23</u>	<u>29</u>	<u>30</u>	<u>36</u>	<u>42</u>	<u>47</u>
<u>Type</u>		<u>A1</u>	<u>A1</u>	<u>A1</u>	<u>A2</u>	<u>A2</u>	<u>A2</u>	<u>A2</u>
GAWR (Pounds)	Front Rear	4,300 7800	4,600 9,450	4,600 9,450	4,600 9,860	6,000 15,500	6,000 15,500	8,000 15,500
GVWR (Pounds)		11,500	14,050	14,050	14,500	21,500	21,500	21,500
Minimum engine size for diesel engines		6.0L	6.0L	6.0L	6.0L	6.0L	6.0L	6.0L
Approximate wheelbase (inches)		139	139	152	152	170	194	202
Minimum fuel tank, gallons		30	30	30	35	35	35	60
Minimum	Tires*	LT225/75R16, LR. D	LT225/75R16, LR. D	LT225/75R16 LR. D	225/70R19.5 LR. F	225/70R19.5 LR. F	225/70R19.5 LR. F	225/70R19.5 LR. F
		6.0 X 16	6.0 X 16	6.0 X 16	6.75 x 19.5	6.75 x 19.5	6.75 x 19.5	6.75 x 19.5
Transmission minimum specifications Rims		Automatic 4 Speed	Automatic 4 Speed	Automatic 4 Speed	Allison PTS 2200	Allison PTS 2200	Allison PTS 2200	Allison PTS 2200
Alternator minimum amps		120	120	120	160	160	160	160

* Low-profile tubeless radial tires of size and load range meeting Tire and Rim Association Standards for the required GAWRs may be approved in lieu of standard conventional tubeless radial tires. Minimum tire sizes specified above are to be supplied as standard equipment, unless specific approval is granted for use of low-profile sizes.

SPECIFICATIONS for OPTIONAL CHASSIS EQUIPMENT for TYPE A BUSES

1. **AIR-SPRUNG REAR SUSPENSION SYSTEM**

Option for air-ride or approved equivalent air-sprung rear suspension system, when available from chassis manufacturer. Shall have rear GAWR greater than or equal to standard specifications requirements for the type and capacity of chassis on which it is installed. Rear shock absorbers also required with this option, as on standard suspension systems.

2. **FRONT BUMPER FLEXIBLE ENDS**

Option for front bumper with flexible end caps meeting all other requirements of these specifications for front bumper.

3. **HIGHER OUTPUT ALTERNATOR**

Option for an alternator having a minimum of 270 amps hot rated output.

4. **LOW-PROFILE RADIAL TIRES**

Option for all-wheel-position, highway-ribbed, low-profile, tubeless radial tires of size and load range meeting Tire and Rim Association Standards for the required GAWRs.

5. **SPARE DISC WHEEL**

Option must be same size and type as original rims.

6. **TOW HOOKS**

There shall be two subcategories for this option. (1) Two heavy-duty front tow hooks. Each hook shall be installed by manufacturer, in an approved manner to each frame rail. (2) Two heavy-duty rear tow hooks. Each hook shall be installed by manufacturer, in an approved manner, to each frame rail.

7. **STRAIGHT FLOOR CHASSIS**

Option for Type A chassis to accept straight floor bodies (i.e., no wheel wells). This type chassis must have a combination of axles, suspension, tires and wheels, and axle stops such that the maximum upward travel of the rear suspension in normal straight-ahead driving does not protrude above the top of the frame rails.

8. **AUTOMATIC TRANSMISSION WARRANTY**

Option for extension of transmission warranty to 5 years, unlimited mileage, 100 percent parts and labor.

SECTION II
TYPE B, C, AND D CHASSIS
SPECIFICATIONS

BASIC MINIMUM SPECIFICATIONS FOR SCHOOL BUS CHASSIS FOR MOUNTING TYPE B, C, and D SCHOOL BUS BODIES

1. ALTERNATOR

160 amps minimum; 50 amps minimum output at manufacturer's recommended engine idle speed; dual belts or poly-vee type belt, maximum ratio 3.0 to 1; sealed ball or roller bearings, meeting National School Transportation Specifications and Procedures. Direct gear driven alternator is an approved equal.

All chassis on which lift bodies are to be mounted shall be equipped with an alternator producing at least 75 amperes current output at chassis manufacturer's recommended engine idle speed, while maintaining chassis manufacturer's recommended regulated voltage.

All chassis on which an air conditioner is to be installed shall be equipped with a minimum 200 amp alternator.

2. BATTERY(IES)

Diesel: Total of 1,750 CCA minimum at 0°F, 12 volt; temporary frame mount location and mounted in a slide-out tray in body skirt for Type B and D.

3. BRAKE, PARKING

On hydraulic brake models an Orscheln-type control, or approved equal, mounted for easy access by the driver is required. On air brake models, a dash-mounted control valve to spring-set the parking brake on the rear wheels is required.

Type C, 29 capacity light buses may be equipped with a hydraulically actuated parking brake assembly.

NOTE: All chassis, 47 capacity and larger, on which a wheelchair lift body is to be mounted, shall be equipped with a park brake operating by means of rear wheel brake shoe or pad mechanical actuation.

4. BRAKES, SERVICE

a. Hydraulic Brakes, Type B, C, and D Front Engine: Acceptable only on 29-35 capacity Type B, 29-41 capacity Type C, and 41 capacity Type D front engine; must have approved power assist and meet all applicable requirements of National School Transportation Specifications and Procedures, Revised 2005, and applicable Federal Motor Vehicle Safety Standards. Brake lining material shall not contain asbestos. Type B, C, and D buses equipped with hydraulic brakes shall be equipped with the manufacturer's standard antilock brake system.

b. Air Brakes, Type B, C, and D: Air brakes are required on all Type B buses larger than 35 capacity, Type C and D front engine buses larger than 41 capacity, and all Type D rear engine buses. Air brake models shall meet National School Transportation Specifications and Procedures, Revised 2005, and all applicable Federal Motor Vehicle Safety Standards.

A minimum 12 CFM, engine oil-fed air compressor is required on all air brake models. Clean air to the air compressor shall be supplied from "clean" side of engine air cleaner or air system. Compressor shall not be equipped with separate, compressor-mounted air filter. Air brake models shall be equipped with a desiccant air dryer with an automatic purge and drain cycle and a heating element. Air brake system design shall provide for anti-compounding of service and emergency brakes, and spring brake modulation upon application of front service brakes in event of loss of air pressure to rear service brakes. All hoses used in the air brake system shall be constructed of nylon tubing that is SAE J844 Type A or B, DOT FMVSS 106 compliant, and shall be color-coded. Antilock Braking System with independent controls for each wheel position.

All air brake equipped chassis, including air disc/drum or air disc, must be equipped with a spring-set parking brake on the rear wheels. Drum brakes shall be cam-actuated and brake S-cam rotation must be in same direction as forward wheel rotation. All slack adjusters (as equipped) shall be automatic adjustment type. All brake drums shall be outboard mounted; i.e., drums shall be removable without removal of the axle hub. Rear axle of all Type B and C buses with air brakes shall be equipped with grease guards to divert excessive oil or grease leaks away from brake linings in the event of a rear wheel seal leak or the bidder shall provide warranty of rear axle seals and brake components as noted in the Chassis Warranties section. All air brake chambers less than Type 20 shall have at least a 2.5 inch stroke. All air brake chambers of Type 20 or greater shall have at least a 3.0 inch stroke. All spring brake chambers shall be equipped with a spring brake caging device.

Brake lining material shall not contain asbestos. Minimum lining thickness on air-actuated drum brakes must be 3/8 inch front and 3/4 inch rear (except taper on brake blocks). All air brake equipped chassis must have a minimum rear brake shoe width of 7 inches.

NOTE: See Chassis Specifications Charts, pages II-9 through II-11, for minimum lining area requirements applicable to hydraulic or air brake chassis equipped with 4 wheel drum brakes.

5. **BUMPER, FRONT**

Must be black, full width, channel type, minimum 8 inches, of sufficient structural and mounting strength to ensure that front of vehicle may be lifted by means of an air bumper-type jack, without permanent deformation of the bumper, brackets, or chassis frame rail(s).

6. **COMPONENT ACCESSORY DRIVE**

Components, such as alternator, air compressor, and power steering, shall deliver to rated requirements without drive slippage at maximum load.

7. **DIFFERENTIAL RATIO**

Shall be compatible with engine and provide for 60 mph in highest gear. Also see ENGINE PERFORMANCE, page II-5, and TRANSMISSION, AUTOMATIC, page II-8.

8. **DRIVESHAFT GUARDS AND SHIELDS**

Required. At least 1 per driveshaft section.

9. **ENGINE EQUIPMENT**

a. Configuration: Diesel engines shall be available in at least one of the following two configurations:

- (1) Parent bore type block; in-line 6 cylinder design; minimum 6.4 liters displacement.
- (2) Wet sleeve type block; in-line 6 cylinder design; minimum 6.4 liters displacement.

NOTE: Additional diesel engines of other configurations or displacements (not in lieu of the above) meeting all other requirements listed herein may be offered, subject to approval by the Department of Education.

b. Engine Requirements

- (1) **Dry type air cleaner:** Required. An air filter restriction indicator is required on diesel engines. The restriction indicator shall incorporate a system that does not allow unfiltered air into the engine if the indicator cracks or breaks.
- (2) **Oil filter(s):** Engine shall be equipped with full-flow, spin-on, or cartridge-type oil filter(s), with filter header(s) mounted directly to engine.
- (3) **Engine coolant recovery or deaeration system:** Required on all chassis. Diesel engines must include some means for visually checking coolant level without removing deaeration tank cap or releasing pressure from cooling system.
- (4) **Warning system consisting of light and buzzer:** Required on diesel-powered chassis to notify driver of low engine oil pressure and/or coolant overheating.
- (5) **Fuel filtration/water separation:** Required on diesel engines. The system shall remove all contamination capable of adversely affecting the fuel system from the fuel prior to entry into the engine. The system shall be designed to remove contaminants **normally** found in Florida, including dirt, water, and algae. The system shall be designed with the capacity necessary to last 15,000 miles or more between filter changes. Manufacturers that do not meet this requirement shall be required to provide fuel filters free of charge to districts until they have retrofitted systems that will meet this requirement on all units produced with an inadequate system. Engine or fuel system damage due to inadequate filtration shall be repaired by the manufacturer at no cost to the district. System shall have a clear sight bowl, or be equipped with water-in-fuel light to notify technicians of the presence of water. System must provide a valve for draining trapped water from the system. Fuel system shall include either an electric or a manual priming pump.

- (6) **Oil pressure and coolant temperature gauge:** Oil pressure gauge shall provide accurate, easily discernible readings across the entire operating range from hot idle to full oil pressure. Gauges on engines with idle oil pressure, which under normal conditions is low, shall provide a **clear** distinction between no oil pressure and engine idle oil pressure. Gauges shall be directly visible to driver in normal seated position and shall not be mounted near center of dash where body door control or associated hardware could block visibility.
- (7) **Governor: Shall permit** controlled engine RPM up to manufacturer's recommended maximum for engine used.
- (8) **Ignition switch: Controls** running and shutdown of engine. Running of engine shall require electrical current provided by the ignition switch in the "start" and "run" positions. Engine shutdown shall result when current is cut off (ignition switch in the "off" position).
- (9) **Engine throttle control:** The force **required** to operate the throttle shall not exceed 16 pounds through the full range of accelerator pedal travel.
- (10) **Radiator and other engine coolant hoses** supplied by chassis manufacturer (not including heater hoses) shall be constructed of silicone rubber or hoses with EPDM covering and aramid fiber reinforcement meeting or exceeding SAEJ20R EC Class D-1. Silicone hose, if used, shall require the use of stainless steel shoe-type hose clamps or constant-torque clamps. Hoses shall have markings, coloring, or other visible means of distinguishing them from the standard hoses.
- (11) Manufacturers shall use the largest capacity oil pan available for each engine configuration in order to achieve the longest oil change interval.

10. **ENGINE PERFORMANCE REQUIREMENTS**

- a. Each bus shall be furnished with a power train that meets or exceeds the following minimum criteria when tested at the GVWR required for a given bus capacity, and with all accessories (including air conditioning compressor(s), if equipped) on and operating:
 - (1) Startability of 20 percent.
 - (2) Gradeability of 5 percent at 25 miles per hour.
 - (3) Gradeability of 1.5 percent at 50 miles per hour.
 - (4) Top speed of 60 miles per hour minimum.
- b. Power train shall provide acceleration performance as specified in (3) below. Test conditions are as follows:
 - (1) As generated by an Allison SCAAN with the following parameters used:
 - (a) Vocation file number 2610.
 - (b) At gross vehicle weight for the specific bus size as listed in this manual.
 - (c) Tire size must be tire size listed herein for the specific size of bus.
 - (d) 6 total tires in contact with the road.
 - (e) Total driveline reduction factor used for the SCAAN must equal the reduction supplied in the complete chassis.
 - (f) Driveline efficiency 96.13 percent.
 - (g) Road surface factor 1.200.
 - (h) Vehicle height and width 10 feet X 8 feet.
 - (i) Air resistance coefficient 0.55.
 - (2) As measured with the actual completed vehicle (i.e., with body installed, unloaded except for the driver and one passenger). The vehicle shall be in drive, engine at idle, service brakes applied, emergency brakes released, and all accessories on and operating. Measurement of acceleration time shall begin at the moment the throttle is applied (the throttle is to be immediately and rapidly depressed to full throttle).

NOTE: Chassis manufacturer should use the heaviest chassis/body combination meeting these specifications for the specific size bus to determine required power train componentry. This test is an on-road test and will be performed using the heaviest available chassis/body, depending on body(ies) supplied. At the discretion of the Department, unanticipated factors or variations in test conditions, affecting performance test results, that are beyond the control of the chassis manufacturer may be taken into account. Pro Link, diagnostic computer or speed wheel are also acceptable tools for this test.

- (3) Maximum acceleration time (from zero mph), under conditions specified above, shall be as follows (measured in seconds):

29-77 Capacity Type B, C, and D:

TEST METHOD	0-10 MPH	0-20 MPH	0-30 MPH	0-40 MPH	0-50 MPH
(1) SCAAN	2.9	8.1	16.8	30.1	53.8
(2) ACTUAL	3.4	6.2	12.0	20.0	32.2

78-90 Capacity Type D

TEST METHOD	0-10 MPH	0-20 MPH	0-30 MPH	0-40 MPH	0-50 MPH
(1) SCAAN	2.9	8.1	16.8	30.1	53.8
(2) ACTUAL	3.7	7.1	12.0	20.0	32.2

- (4) Manufacturers may offer additional engine configurations and horsepower ratings that exceed these requirements as optional equipment.

11. EXHAUST SYSTEM

Corrosion resistant muffler and tailpipe; must exit to left of left frame rail and behind rear wheels. Tailpipe must extend 5 inches beyond chassis frame on Type B and C stripped chassis (see 2005 National School Transportation Specifications and Procedures). Chassis manufacturer shall ensure that exhaust design allows exit location left of left frame rail to be maintained after any modifications to frame length by chassis or body manufacturer. Manufacturers must ensure that exhaust temperature exiting the tailpipe during any normal loading or unloading activity with the engine running will not produce first, second, or third degree burns on students or other individuals present. Diesel particulate filter active regeneration shall not occur while the bus is stationary. Also see **Section III, Electrical Equipment and Wiring**.

12. FRAME SIDE MEMBERS

One-piece construction between front and rear spring hangers. All frame rails shall be minimum 50,000 psi tensile strength. Extension of frame length on chassis is permissible only when such alterations are not for purposes of extending or reducing wheelbase.

13. FRONT AXLE LUBRICATION

All buses shall have oil-lubricated front axle hubs providing externally visible check of lubricant level.

14. FUEL TANK

Fuel tank and fuel system shall meet requirements of FMVSS 301. Filler spout shall be located for ease in servicing. Fuel gauge compatible with tank capacity shall be supplied. Tank may be located on the right chassis rail or between the frame rails. Filler neck shall be located on the right side of the bus unless other locations are pre-approved by the Department. See **Chassis Specifications Charts, pages II-9 through II-11**, for required fuel tank capacity.

15. **HEADLIGHTS**

1. Must meet SAE and Federal Standards and shall use a quartz halogen bulb. All units must be equipped with Full-Time Lights (FTL) meeting the following requirements:
 - a. With the ignition switch off, the headlights will operate normally and the FTL system will not operate.
 - b. With the ignition switch on or in the accessory position, and with the engine not running, the FTL system shall not operate.
 - c. With the ignition switch on and the engine running and with the headlight switch off, the FTL system must operate, providing low beam headlights, tail, clearance, and ID lights. This activation may be accomplished by any reasonable means including the use of the park brake system.
 - d. In all cases the headlight switch must override the FTL system when in the “on” position.
 - e. This system shall include a buzzer that activates if the headlight system is on with the key switch in the “off” position.

16. **HOOD**

Engine hood on Type B and C buses shall not require more than 20 pounds of force to open or close.

17. **HORNS**

Dual, 120 decibels (see National School Transportation Specifications and Procedures).

18. **IGNITION SYSTEM**

All ignition switches shall be keyed alike. All buses of like chassis manufacturer and type shall have one key.

19. **INSULATION**

Type B and C chassis shall include full width and height heat and noise insulation on the inside or outside of the bus covering the dash panel (firewall) area to as great an extent as possible and at least up to the top of the firewall and down to the point that the body floor connects to the firewall, including engine cover (doghouse). Type D Front Engine buses shall include complete heat and noise insulation of the doghouse area.

20. **LINE-SETT TICKET**

Manufacturer shall include with delivery of vehicle a line-sett ticket to accurately reflect the following: a) all chassis components; b) GAWR of both front and rear axles; and, c) GVWR.

21. **ODOMETER**

Accrued mileage, 7 digits, including tenths of miles (999,999.9 mile odometer).

22. **PAINT AND FINISH, TYPE B, C, and D CHASSIS**

Prior to the application of the finish coats to chassis hood, fenders, and cowl, all surfaces shall be cleaned of grease, foreign matter, excess caulking and sealing material, and treated as per paint manufacturer's recommendation for proper paint adhesion. School bus yellow paint shall meet SBMTC-008 for color and shall have a finished gloss rating of at least 85 at 60° and a distinctness of image rating of an average of at least 50 measured using the same method specified for gloss under **WARRANTIES**. Paint shall be applied for a total dry thickness of at least 1.8 mils over all painted surfaces. Trim, lettering, and bumper shall be black except that bumper may be striped with reflective material in accordance with National School Transportation Specifications and Procedures or these specifications. Rims for all Type B, C, and D buses with hub-piloted wheels (required on Type B, C, and D buses built pursuant to these specifications) shall be powder-coated at the wheel manufacturer, National School Bus Yellow. All stud-piloted rims shall be painted black. Lug nuts shall not be painted. Lead-free paint shall be used on all interior and exterior surfaces of the body and chassis. Also see **WARRANTIES, page 12**, for warranty requirements.

23. **RADIATOR FILLER TUBE**

Located for ease of service from engine compartment on Type B, Type C, and Type D rear engine. Shall be located for ease of service from outside of bus on Type D front engine.

24. **SHOCK ABSORBERS**

Front and rear, double acting; adequate size for axle load.

25. **SPRINGS, FRONT, TYPE C**

Double-wrap stationary end (see **Chassis Specifications Charts, pages II-9 through II-11**, for spring weight rating requirements).

26. **SPRINGS, REAR, TYPE C**

Progressive type (see **Chassis Specifications Charts, pages II-9 through II-11**, for spring weight rating requirements).

27. **STEERING**

Integral type power steering required. A tilt steering wheel/column is required.

28. **TIRES AND RIMS**

Chassis shall be equipped with radial tubeless tires mounted on hub-piloted disc wheels. All wheels of 8.25 inches or greater width shall be 2 hand-hole wheels. Tires and rims shall conform to current standards of Tire and Rim Association (see **Chassis Specifications Charts, pages II-9 through II-11**, for sizes). See **PAINT AND FINISH, page II-7**, for wheel color information.

29. **TRANSMISSION, AUTOMATIC**

An automatic transmission is required on all chassis as specified:

- a. Type B 29-35 capacity, Allison PTS 2100, 5 speed or approved equal.
- b. Type B 47-71 capacity front engine, Allison PTS 2500, 5 speed or approved equal.
- c. Type C 29-71 capacity, Allison PTS 2500, 5 speed or approved equal.
- d. Type B and C 77 capacity, Allison PTS 3000, 5 speed or approved equal.
- e. Type D 41-71 capacity front engine, Allison PTS 2500, 5 speed or approved equal.
- f. Type D 78-89 capacity front engine, Allison PTS 3000, 5 speed or approved equal.
- g. Type D 60-72 capacity rear engine, Allison PTS 2500, 5 speed or approved equal.
- h. Type D 78-89 capacity rear engine, Allison PTS 3000, 6 speed or approved equal.

Allison PTS 2000 series transmissions must include an external spin-on type, vertically mounted, transmission fluid filter. Shifter shall be dash or console mounted and shall be either T-handle or push-button design.

Allison PTS 3000 series transmissions shall have at least 5 speeds enabled for front engine Type D and 6 speeds for rear engine Type D. Type D front engine chassis with PTS 3000 series transmissions shall have a 6.0:1 or higher rear end ratio; Type D rear engine chassis with PTS 3000 series transmissions shall have a 6.5:1 or higher rear end ratio. Push-button shifting control shall be used on PTS 3000 transmissions. PTS 3000 series transmissions shall include a transmission fluid filter externally accessible without removal of the transmission oil pan.

30. **TURN SIGNALS**

Dash indicator lights and self-canceling switch with lead wires on steering column for body manufacturer's attachment shall be installed by the chassis manufacturer. Type B and C buses shall have front turn signal assemblies installed by the chassis manufacturer integrated into the headlight assembly or, if not available, fender mounted turn signal lights.

31. **VOLTAGE CONTROL**

A voltage regulator shall be required, equipped with solid state components (transistorized), and readily accessible. A voltmeter with a graduated scale is also required.

32. **WARRANTIES**

See required chassis warranties on page 12.

33. **WIRING HARNESS**

All chassis electrical wiring must be completely encased in convoluted loom or equivalent protective wrapping. In locations that prevent such looming, wires shall be properly held in place by appropriate fasteners at intervals necessary to prevent possible damage to wire insulation.. 100 amp load and complete wiring for tail and stop lights; color-coded circuits. Fuse box door, if equipped, shall have a positive latch. All chassis circuits above 5 amps shall be protected by manually resettable circuit breakers except as otherwise required by FMVSS. Buses using multiplexed electrical systems may meet the intent of these specifications without the use of specified equipment, subject to approval by the Department.

TYPE C DIESEL CHASSIS

<u>Maximum Design (Passenger) Capacity</u>	<u>29LT</u>	<u>29</u>	<u>47</u>	<u>53</u>	<u>59</u>	<u>65</u>	<u>71</u>	<u>77</u>
Minimum Gross Axle Weight Rating (pounds)								
A. Front	5,000	6,000	7,000	7,800	9,000	9,000	10,000	10,000
B. Rear	10,000	12,400	14,200	16,160	19,000	19,000	19,000	20,000
Cowl to axle, minimum (inches)	123	123	162	194	211	229	250	250
Approximate wheelbase (inches)	150	150	190	218	239	254	254 or 276	276
Front axle pound minimum	5,000	6,000	7,000	8,000	10,000	10,000	10,000	10,000
Rear axle pound minimum	10,000	13,000	15,000	17,000	19,000	19,000	19,000	21,000
Each front spring at ground	2,500	3,000	3,500	4,000	4,500	4,500	5,000	5,000
Each rear spring at ground, progressive springs	5,000	6,500	7,500	8,500	9,500	9,500	9,500	10,500
Service brake-drum brake only (minimum total square inch)								
Hydraulic	440	440	NA	NA	NA	NA	NA	NA
Full air	NA	663	663	663	663	663	663	663
Minimum tire size: tubeless-radial ply*	225R-19.5F	10R-22.5-F	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G
Minimum wheel rim size	6.75	7.5	8.25	8.25	8.25	8.25	8.25	8.25
Hub-piloted disc wheels for tubeless radial tires	6 stud, 5 hand hold	6 stud	10 stud	10 stud	10 stud	10 stud	10 stud	10 stud
Allison transmission series (# of forward gears)	PTS 1000 or 2200 (5)**	PTS 2100 (5)	PTS 2100 (5)	PTS 2100 (5)	PTS 2500 (5)	PTS 2500 (5)	PTS 2500 (5)	PTS 3000 (5)
Fuel tank minimum size (gallons)	30	30	60	60	60	60	60	60

- **Low-profile tubeless radial tires of size and load range meeting Tire and Rim Association Standards for the required GAWRs may be approved in lieu of standard conventional tubeless radial tires. Minimum tire sizes specified above are to be supplied as standard equipment, unless specific approval is granted for use of low-profile tires.**
- **** Shall include park pawl.**

TYPE B MODIFIED FORWARD CONTROL

<u>Maximum Design (Passenger) Capacity</u>	<u>29</u>	<u>35</u>	<u>47</u>	<u>59</u>	<u>65</u>	<u>71</u>	<u>77</u>
Minimum Gross Axle Weight Rating (pounds)							
Front	6,000	6,000	7,500	10,000	10,000	10,000	10,000
Rear	10,500	10,500	15,000	19,000	19,000	19,000	20,000
Gross Vehicle Weight Rating (GVWR)	16,500	16,500	22,500	29,000	29,000	29,000	30,000
Service brake- (minimum total square inch)	663	663	663	663	663	663	663
Tires – minimum size acceptable*	225/70R19.5E	225/70R19.5E	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G
Disc wheels -minimum rim width (inches)	6.75	6.75	8.25	8.25	8.25	8.25	8.25
Approximate wheelbase (inches)	138	152	190	235	254	254 – 276	254 – 276
Minimum size fuel tank (gallons)	30	30	60	60	60	60	60
Allison transmission series (# of Forward Gears)	PTS 2100 (5)	PTS 2100 (5)	PTS 2100 (5)	PTS 2500 (5)	PTS 2500 (5)	PTS 2500 (5)	PTS 3000 (5)

TYPE D FORWARD CONTROL FRONT ENGINE

Maximum Design (Passenger) Capacity (Cap.)	41-53	59-71	77	83	89
Minimum Gross Axle Weight Rating (pounds)					
Front	10,800	10,800	12,000	12,000	12,000
Rear	17,000	17,000	19,000	21,000	23,000
Gross Vehicle Weight Rating (GVWR)	27,800	27,800	30,000	33,000	35,000
Service brake- (minimum total square inch)	663	663	750	750	750
Tires – minimum size acceptable*	10R-22.5F	11R-22.5G	11R-22.5G	11R-22.5-G	11R-22.5-G
Disc wheels -minimum rim width (inches)	7.5	8.25	8.25	8.25	8.25
Approximate wheelbase (inches)	131 – 161	159 – 201	212 – 217	227 – 237	245 – 254
Minimum size fuel tank (gallons) meeting requirements of FMVSS.301	45 (41-47 cap.) 60 (53-cap.)	60	60	60	60
Allison transmission series (# of forward gears)	PTS 2500 (5)	PTS 2500 (5)	PTS 3000 (5)	PTS 3000 (5)	PTS 3000 (5)

NOTES: 1) Automatic transmission is required on all chassis. See TRANSMISSION, AUTOMATIC, page II-8, for required specifications.

2) Maximum overall length of vehicle shall not exceed 45 feet, bumper to bumper.

3) *Low-profile tubeless radial tires of size and load range meeting Tire and Rim Association Standards for the required GAWRs may be approved in lieu of standard conventional tubeless radial tires.

TYPE D REAR ENGINE CHASSIS SPECIFICATIONS CHART

Maximum Design (Passenger) Capacity	60	66	72	78	84	90
Minimum Gross Axle Weight Rating (pounds):						
A. Front	11,000	11,000	11,000	12,000	12,000	12,000
B. Rear	19,000	19,000	19,000	21,000	23,000	23,000
Gross Vehicle Weight Rating (GVWR)	30,000	30,000	30,000	33,000	35,000	35,000
Service brake-drum brake only (minimum total square inch)	663	663	663	750	750	750
Tires – minimum size acceptable *	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G	11R-22.5-G
Hub-piloted disc wheels-10 stud, minimum rim width	8.25	8.25	8.25	8.25	8.25	8.25
Approximate wheelbase (inches)	165 – 184	181 – 228	209 – 242	238 – 256	260 – 284	260 – 284
Minimum size fuel tank (gallons)	60 gal.	60 gal.	60 gal.	60 gal.	60 gal.	60 gal.
Allison transmission series (# of forward gears)	PTS 2500 (5)	PTS 2500 (5)	PTS 2500 (5)	PTS 3000 (6)	PTS 3000 (6)	PTS 3000 (6)

NOTE: Maximum length of vehicle shall not exceed 45 feet, bumper to bumper.

*** Shall meet Tire and Rim Association Standards. Low-profile tubeless radial tires of size and load range meeting Tire and Rim Association Standards for the required GAWRs may be approved in lieu of standard conventional tubeless radial tires.**

SPECIFICATIONS FOR OPTIONAL CHASSIS EQUIPMENT IN TYPE B, C, AND D BUSES

1. **AIR BRAKES**

Option for all sizes and types when hydraulic brakes are standard.

2. **AIR-SPRUNG REAR SUSPENSION SYSTEM**

Option for air-ride or approved equivalent air-sprung rear suspension system, when available from chassis manufacturer. Shall have rear GAWR greater than or equal to standard specifications requirements for the type and capacity of chassis on which it is installed. Rear shock absorbers also required with this option, as on standard suspension systems.

3. **ALTERNATOR, HIGHER OUTPUT**

Option for alternators having a minimum of 200 and 270 amps hot rated output.

4. **FRONT BUMPER FLEXIBLE ENDS**

Option for front bumper with flexible end caps meeting all other requirements of these specifications for front bumper.

5. **LOW-PROFILE RADIAL TIRES**

Option for all-wheel-position, highway-ribbed, low-profile tubeless radial tires of size and load range meeting Tire and Rim Association Standards for the required GAWRs.

6. **LARGER CAPACITY FUEL TANK**

Option for larger fuel tank, mounted on the right side or between the frame rails, when available.

7. **SPARE DISC WHEEL**

Option must be same size, type, and color as original rims.

8. **TOW HOOKS**

2 heavy-duty tow hooks, installed by manufacturer on each frame rail at front of bus in an approved manner. Manufacturer may also offer rear mounted tow hooks meeting the above requirements.

9. **STRAIGHT FLOOR CHASSIS**

Option for chassis to accept straight floor bodies (i.e., no wheel wells). This type chassis must have a combination of axles, suspension, tires and wheels, and axle stops such that the maximum upward travel of the rear suspension in normal straight-ahead driving does not protrude above the top of the frame rails.

10. **AUTOMATIC TRANSMISSION WARRANTY**

Option for extension of transmission warranty to 5 years, unlimited mileage, 100 percent parts and labor.

11. **ADJUSTABLE CONTROL PEDALS**

Option for accelerator and brake control pedals to be adjustable to accommodate different sizes of drivers.

12. **TRANSMISSION FLUID**

Option to have original fill of the transmission with Transynd or approved equal transmission fluid.

13. **TIRES**

Option for alternate brand, size, and tread design of tires when available, but must meet GAWR requirements and Tire and Rim Association Standards.

14. **SILICONE COOLANT HOSES**

Option for radiator and coolant hoses manufactured using silicone rubber.

15. **AUTO HEADLAMP SYSTEM**

Option for auto headlamp system that meets the requirements below:

Unit must be equipped with Daytime Running Lights (DRL) meeting the following requirements:
Must meet applicable SAE and Federal Standards for Daytime Running Lights.

With the ignition switch off the headlights will operate normally and the DRL system will not operate.

With the ignition switch on, or in the accessory position, and the engine not running, the daytime running lights shall not operate.

With the ignition switch on and the engine running, and with the headlight switch off, the DRL system must operate, providing voltage to a dedicated daytime running lamp. This activation may be accomplished by any reasonable means including the use of the park brake system.

Headlight system including tail, ID and marker lights, shall automatically activate at full intensity anytime the vehicle is in operation during low light conditions. These lights shall also activate anytime the windshield wipers are operating.

This system shall include a buzzer that activates if the headlight system is on with the key switch in the "off" position.

In all cases, the headlight switch must override the DRL system when in the "on" position.

SECTION III

BODY SPECIFICATIONS

TYPE A1, A2, B, C, AND D BUSES

MINIMUM FLORIDA SCHOOL BUS BODY SPECIFICATIONS

The specifications set forth in this section are descriptive of Types A1 (19-29 capacity with dual rear wheels), A2 (30-47 capacity) B, C, and D school buses. Special exceptions for Type B and D bodies are listed at the end of this section. The design of school bus bodies is to provide for the safety and comfort of pupils and for economical transportation as required by Florida Statutes and Federal Motor Vehicle Safety Standards. The National School Transportation Specifications and Procedures, 2005 Revised Edition, are applicable for items not specified in this document, storage compartment and tow hooks excepted. References to bus capacity within these specifications are for Maximum Design Capacity, as defined below under **BODY DATA PLATE**.

1. **BATTERY SLIDE-OUT TRAY**

A slide-out tray and battery box is required for the batteries on all Type A, B, C, and D bodies. Access to the batteries shall be through a door in the body. Battery cables shall be long enough to allow the battery tray to be fully extended.

All Type B, C, and D Forward Control bodies equipped with air conditioner shall also be equipped with a compartment mounted next to the battery box with external access for mounting circuit breakers and control circuitry for this option.

There shall be a battery disconnect switch in the A/C or battery compartment or within three feet of the battery box if no A/C box is available. This switch shall be accessible and operable from the exterior of the bus.

2. **BODY DATA PLATE**

A durable body data plate shall be mounted inside the body in a clearly visible location. Body data plate information shall include (in part) a listing of the "Maximum Design Capacity" and the "Equipped Capacity" of the body. Maximum Design Capacity shall be the maximum number of passengers the bus (body shell size) can carry; based on 12.8 inch minimum seat width per passenger with the minimum knee room (seat spacing) required under **SEATING AND MODESTY PANELS, page III-18**. Equipped Capacity shall be the actual passenger capacity of the finished body, as equipped by the manufacturer, based on:

- a. The number of total passengers the installed bench seats are designed to carry, and,
- b. The number of wheelchair positions installed (based on wheelchair space dimensions contained in Section IV of these specifications).

An example of the format to be used for Equipped Capacity is "28 + 3 WC," meaning 28 regular passenger seating positions plus 3 wheelchair positions.

3. **BODY FLUID CLEANUP KIT**

Each bus shall be equipped with a disposable, sealed body fluid cleanup kit in a disposable container with the following items:

- An EPA registered liquid germicide (tuberculicidal) disinfectant
- A fully disposable wiping cloth
- A water resistant spatula
- Step-by-step directions
- Absorbent material with odor counteractant
- 2 pairs gloves (Nitrile)
- 1 package towelettes
- A discard bag (non-labeled paper bag with plastic liner and a twist tie). This bag shall be approximately 4 inch x 6 inch x 14 inch, and of a non-safety color (i.e., not red, orange, or yellow).

The kit shall be mounted by a method that will retain it under a load equivalent to 20 times the weight of the kit and shall be removable without the use of tools. The kit shall be accessible to the driver. The kit container shall be sealed with a breakable, nonreusable seal.

4. BUMPER, REAR

Rear bumper shall be of pressed steel channel at least 3/16 inch thick, 8 inch high, and flanged 2 inches at top and bottom or otherwise designed to furnish equal flexural strength. It shall be of wraparound design and securely fastened to each chassis rail and braced from each end of bumper to chassis rail with heavy braces to permit fully loaded bus to be pushed without permanent distortion to bumper, chassis, or body. The bumper shall also have the structure and strength necessary to allow the unloaded vehicle to be lifted with a bumper jack without deformation or damage. Contour of bumper shall fit contour of body in a manner to prevent hitching to or riding on bumper. An appropriate seal shall be applied between bumper and body panel, unless the gap between bumper and body panel is 1/8 inch or less.

5. DRIVER'S DOCUMENT COMPARTMENT

On Type B, C, and D buses a pouch on the front side of the driver's side crash barrier with minimum dimensions of 17 inch x 12 inch x 4 inch is required. This pouch shall be located to the left side of the barrier for Type B and C, and to the right side of the barrier for Type D, accessible to the driver from the seated position. It shall be made of the same material as the covering on the barrier and have a lid or cover with a latching device such as Velcro™ or snaps.

6. DRIVER'S SEAT AND SEAT BELT

- a. All Type A2, B, C, and D school buses shall have a driver's seat equipped with a one-piece high back designed to minimize the potential for head and neck injuries in rear impacts, providing minimum obstruction to the driver's view of passengers, and meeting applicable requirements of Federal Motor Vehicle Safety Standard 222. The height of the seat back shall be sufficient to provide the specified protection for up to a 95th percentile adult male, as defined in FMVSS 208. The driver contact area of the cushion and seat back shall be made of soil and wear-resistant cloth material, nylon, or equivalent. Remainder of seat may be of a different material. Seat shall be centered behind the steering wheel with backrest a minimum distance of 11 inches behind the steering wheel. Seat shall be securely mounted to ensure minimal flexing of the seat and the floor panel(s).
- b. All air brake equipped school buses shall be equipped with an air suspension driver's seat meeting the following additional requirements:
 - (1) The air control for height adjustment shall be within easy reach of the driver in the seated position.
 - (2) Seat cushion shall be a minimum of 19 1/2 inches wide, shall be fully contoured for maximum comfort, and shall have a minimum of 4 adjustment positions to allow adjustment of seat bottom angle.
 - (3) Backrest shall include adjustable lumbar support.
 - (4) The seat shall have a minimum of 7 inches fore and aft travel, adjustable with the driver in the seated position. This requirement applies to the seat mechanism. Reduction of this requirement to no less than 4 inches fore and aft travel due to barrier placement on 89 capacity buses is acceptable.
 - (5) The seat shall have a minimum 4 inches up and down travel.
 - (6) Seat back shall include adjustability of tilt angle.
 - (7) All adjustments shall be by fingertip controls without the use of tools.
 - (8) Air suspension seats shall be dampened by dual shock absorbers acting independently.
 - (9) The seat shall comply with all applicable Federal Motor Vehicle Safety Standards.
- c. All other buses shall have a driver's seat equipped with a hydraulic and/or spring suspension base, and a minimum seat cushion width of 19 inches, and shall meet the other requirements listed herein for air suspension seats.
- d. Chassis manufacturer's standard driver's seat is acceptable for Type A1 buses.
- e. Overall seat design shall be approved by the Department of Education. Also, see **WARRANTIES, page 12.**

- f. Buses shall be equipped with a Type 2 lap belt/shoulder harness seat belt assembly for the driver. The design shall incorporate a fixed female push-button type latch on the right side at seat level, and a male locking bar tongue on the left retracting side. The assembly shall be equipped with a single, dual sensitive Emergency Locking Retractor (ELR) for the lap and shoulder belt. This system shall be designed to minimize cinching down on suspension type seats. The lap portion of the belt shall be anchored or guided at the seat frame by a metal loop or other such device attached to the right side of the seat to prevent the driver from sliding sideways out of the seat. There shall be a minimum of 7 inches of adjustment of the "D" loop of the driver's shoulder harness designed to provide adequate adjustment for all sizes of drivers within the range of a 5th percentile female to a 95th percentile adult male. Shoulder belt tension shall be no greater than is necessary to provide reliable retraction of the belt and removal of excess slack. The seat belt assembly and anchorage shall meet applicable Federal Motor Vehicle Safety Standards. Seat belt material shall be bright orange or lime green in color, in order to provide maximum contrast with the driver's clothing.

NOTE: Driver's seat belt assembly for Type A1 buses shall be manufacturer's standard Type 2 driver seat belt, meeting applicable FMVSS for school buses 10,000 pounds GVWR and less.

7. ELECTRICAL EQUIPMENT AND WIRING

All wiring shall conform to current standards of the Society of Automotive Engineers, be coded by color, and be insulated. All joints shall be soldered or joined by equally effective fasteners. All wires of 4 gauge or thicker and any accessory wire connected directly to the battery shall have soldered ends, and the ends shall be protected with heat shrink tubing. Body wiring and connectors, including any battery cables routed by the body manufacturer, shall be routed so as to eliminate possibility of wiring and connectors becoming abraded, pierced by fasteners, shorted, or otherwise damaged during manufacture and use. All chassis and body electrical wiring shall be completely encased in convoluted loom or equivalent protective wrapping. In locations that prevent such looming, wires shall be properly held in place by appropriate fasteners at intervals necessary to prevent possible damage to wire insulation. A complete body wiring diagram showing location of wires and code of circuits for buses meeting Florida Specifications shall be installed in each body. Additionally, for all school bus body optional electronic components installed in the bus, the body manufacturer shall provide each district with at least one comprehensive parts and repair manual. Buses using multiplexed electrical systems may meet the intent of these specifications without the use of specified equipment subject to approval by the Department. All requirements listed herein for Light Emitting Diode (LED) type lights shall be for the latest generation LEDs available at the time of manufacture. Electrical components specified below shall be provided and wiring shall be in circuits as follows:

a. ACCESS PANEL, ELECTRICAL

All Type B and D buses shall be equipped with an exterior electrical access panel to provide easy access to body electrical components and circuits.

All Type C buses shall be equipped with an exterior electrical access panel or must provide easy internal access to body electrical components and circuits.

b. BACKUP LIGHTS; BACKUP ALARM and STICKER

- (1) There shall be 2 backup lights of 4 inch diameter, or 12.5 square inches, on the rear of all bodies meeting the following requirements:
 - (a) Sealed incandescent or LED type light.
 - (b) Universal type sealed electrical plug connector.
 - (c) Inset into the bus body (flush mounted).
- (2) Body manufacturer shall provide a backup alarm on each bus to provide audible warning that the bus is in reverse gear. Alarm shall meet requirements of SAE J994, and shall have a variable volume feature that allows the alarm to vary from 87 dBA to 112 dBA sound level, staying at least 5 dBA above the ambient noise level. All buses shall have a sticker affixed to the dash in full view of the driver indicating that the bus is equipped with a backup alarm.

c. BRAKE/TAIL LAMPS, LARGE

- (1) Buses shall be equipped with 2 combination brake/tail lamps of a minimum of 7 inches in diameter or, 38 square inches, mounted as high and spaced as far apart laterally as practical, below window line, but not less than 3 feet measured from center of lamps.
- (2) Brake/tail lamps shall be LED type lights.
- (3) Lamps shall use a universal type sealed plug connector.

- (4) Lamps shall meet current SAE requirements and be installed in compliance with Federal Motor Vehicle Safety Standards.

d. **BRAKE/TAIL LAMPS, SMALL**

Bus shall be equipped with 2 combination brake/tail lamps of 4 inch diameter or 12.5 square inches, meeting Federal Motor Vehicle Safety Standards. Light intensity shall at least equal Class A type turn signal units. These lights shall be LED type lights with smooth exterior lens surfaces. They shall use a universal type sealed plug connector and be inset into the bus body.

e. **CIRCUIT BREAKERS**

All body electrical circuits of more than 5 amps shall be equipped with manual resetting circuit breakers except as otherwise required by FMVSS. Circuits of 5 amps or less may be fused. The main body electrical circuit shall be protected by a manually resettable circuit breaker or fusible link.

f. **CLEARANCE AND IDENTIFICATION LIGHTS**

- (1) Clearance lights shall be mounted at the four body corners, upper section, amber front, and red rear. Intermediate amber units required on all units over 30 feet. Clearance lights shall be activated by headlight switch.
- (2) Identification lights shall be mounted as follows: 3 amber lights in front and 3 red lights in the rear, grouped in a horizontal row. Lamp centers shall be spaced no less than 6 or more than 12 inches apart, mounted as close as practical to the vertical centerline. Identification lights shall be activated by headlight switch.
- (3) All clearance and identification lights shall meet current SAE requirements and Federal Motor Vehicle Safety Standards and shall:
 - (a) Be sealed type lights with vibration and shock absorbing bulb mounting.
 - (b) Be surface mounted with Lexan™ or other polycarbonate material guard to prevent breakage. Lights inset into the body do not require guards and may be LED type lights.
 - (c) Use a universal type sealed electrical plug connector.

g. **CONTROL PANEL LIGHTING**

The control panel or switches supplied by the body manufacturer shall be illuminated, and shall have a control for varying the illumination to the control panel or switches.

h. **POST-TRIP PASSENGER CHECK SYSTEM**

(1) **System Requirements:**

Bus shall be equipped with a system to require the driver to walk to the rearmost interior of the bus after each trip to deactivate the system via push button and to ensure that no passengers are left on the bus. The system shall interconnect with the entrance door, and the driver's door on Type A buses, and immediately activate if the door is opened when the system is armed.

System shall be armed any time the bus is in service transporting students. This may be accomplished through use of any reasonable method, such as speed above 20 MPH or 10 minutes of operation with the door closed. In all cases the system shall arm itself after 10 minutes of operation. The system should not normally arm during shop maintenance.

The system may not be disarmed until the vehicle ignition switch has been switched to the "off" position. The system shall not be activated if the ignition switch is placed in the accessory position or if the bus is restarted.

The system must turn on the interior lights when the ignition switch is turned to the "off" position. The lights shall remain on for 60 seconds after system deactivation.

The system shall not have a bypass.

The system shall sound the vehicle horn and flash the headlights if the driver fails to deactivate the system within 60 seconds of turning the ignition off. Type A1 buses may activate the red pupil warning lights in lieu of the headlights if connecting to the headlight circuit interferes with FMVSS compliance.

The system shall be disarmed by the use of a heavy-duty push button placed on the left rear bulkhead or above the left rear passenger window for Type A, B, C, and D FE buses. The push button shall be placed above the left rear passenger window for Type D RE buses. This button shall be clearly marked.

(2) **System Definitions:**

Armed = The state when the system is functioning and is ready to alarm.

Disarmed = The system is off and inactive.

Activated = The state when the horn is blowing and the lights are flashing.

Deactivated = The state achieved when the driver walks to the rear of the bus and operates the disarm switch.

(3) **System Functionality:**

(a) The system must be fully automatic in function and shall not provide for manual bypass or override capability under any circumstances.

(b) From bus sitting still with ignition key in the “off” position:

(i) Ignition key switched to “accessory” position, system remains disarmed.

(ii) Ignition key switched to “on” position (engine remaining off), system remains disarmed.

(iii) Ignition key switched to “on” position (engine running) and bus operated under 20 MPH, system remains disarmed.

(iv) Ignition key switched to “on” position (engine running) and bus operated over 20 MPH or for more than 10 minutes of continuous operation, (or other reasonable operational trigger mechanism), system is armed.

(c) From bus having been operated over 20 MPH, no longer moving, entrance door (and driver’s door, if equipped) closed, ignition key in the “on” position (engine running), and system armed:

(i) Ignition key switched to “off” position (engine off), interior dome lights are immediately illuminated.

(ii) Ignition key switched to “off” position (engine off) and ignition key switched back to “on” position (engine off or restarted) within 60 seconds, interior dome lights are extinguished and the system remains armed but flashing light and horn alarms are not activated.

(iii) Ignition key switched to “off” position (engine off), interior dome lights illuminated and entrance door (or driver’s door, if equipped) opened, flashing light and horn alarms are activated.

(iv) Ignition key switched to “off” position (engine off), interior dome lights illuminated and driver takes no action for 60 seconds, flashing light and horn alarms are activated.

(v) Ignition key switched to “off” position (engine off), interior dome lights illuminated and driver walks to the rear of the bus and disarms system within 60 seconds, system is disarmed and no flashing light and horn alarms are activated.

(d) Once flashing light and horn alarms are activated, they can be deactivated only by disarming the system at the rear of the bus.

(e) Interior dome lights are extinguished 60 seconds after system is disarmed.

i. **DEFOGGER FAN**

A 6 inch defogger fan, in addition to defrosters utilizing hot air from bus heater, shall be installed and mounted to the left side of the windshield, when possible, in a location approved by the Department. A body header-mounted squirrel cage type fan with directable louvers or integrated dash air-conditioning are approved by the Department in lieu of the 6 inch fan.

j. **EMERGENCY DOOR BUZZER**

Emergency door (and window) buzzer shall be connected to accessory side of ignition switch.

k. **HEATER/DEFROSTER**

- (1) There shall be a heater mounted in the front of the bus. A supplemental heater, minimum 80,000 BTU rating, may be installed in any buses. The heat exchanger (core) of any heater shall be constructed to withstand a minimum static test pressure of 300 PSIG without rupture or leakage. All heaters shall meet the following requirements:
 - (a) School bus heating systems shall meet the following performance standards:
 - (i) Provide evenly distributed heat throughout the bus body.
 - (ii) Provide defrosting for windshield and entrance door.
 - (b) Heaters shall have capabilities of providing evenly distributed heat creating a temperature rise to 50° F inside body shell when soaked in ambient temperature of 0° F for 15 hours.
 - (c) Heater performance shall be measured as follows:
 - (i) Temperature measurement taken 39 inches inward from side walls, 39 inches inward from windshield and rear door, and 36 inches above floor. Heat shall be evenly distributed through the aisle area.
 - (ii) Temperature must rise to 50° F inside (when soaked in ambient temperature of 0° F for 15 hours) in 20 minutes when 170° F hot water is applied at the rate of 3 gallons per minute at a maximum of 6 psi pressure.
 - (iii) Maximum current draw for heaters including defrosters shall not exceed 45 amperes.
 - (d) Defrosters – Shall be included in the total electrical load for heaters and meet the following criteria:
 - (i) Shall be able to defrost total windshield area in a reasonable period of time under all normal driving conditions.
 - (ii) Shall be directional to provide driver capability of defrosting in drive view area first.
 - (iii) Defroster system shall have capability of mixing minimum 50 percent outside fresh air with defrosting air.
 - (iv) Defroster system shall meet SAE Standard J381-J382 performance requirement.
- (2) All heater hoses shall be constructed of silicone rubber or hoses with EPDM covering and aramid fiber reinforcement meeting or exceeding SAEJ20R EC Class D-1. If silicone hoses are used, shoe type hose clamps must be used. Heater lines on the interior of the bus shall be shielded to prevent scalding of the driver or passengers. The modesty panels shall not obstruct heat flow from the driver's area to the passenger area of the bus; this may be accomplished by ducting or other means that retains, to the extent practical, required full width aluminized steel panel extending down to floor. Also see **SEATING AND MODESTY PANELS, page III-18.**
- (3) A ¼ turn ballcock type coolant flow regulating valve for the heater shall be installed so that its control is accessible to the driver, but in such a location as to discourage tampering by students. This valve may be remotely located if a suitable remote control system is used. Also required are ¼ turn ballcock type coolant flow regulating shut-off valves, installed in the pressure and return lines as close to the engine as possible.
- (4) The windshield defroster and defogging system shall provide defogging of the entire windshield, driver's side window, and entrance door glasses by utilizing hot air taken from the heater core. Bodies that do not have defrosters providing forced heated air by means of ducting across entire base of windshield must be equipped with an additional right-side mounted defroster fan that utilizes hot air from the heater. One electrical switch shall be provided to simultaneously turn on or off any fan(s) providing hot air for defogging of windshield, driver's side window, and entrance door glass.

NOTE: Type A1 buses shall have a fresh air type heater and defroster system as installed by the chassis manufacturer.

I. INTERIOR LIGHTS

There shall be installed at least 4 recessed flush-mounted interior lights in the passenger compartment of the bus, operated by one control panel mounted switch. If more than 6 lights are used, then an additional switch may be added to control these lights. There shall also be 2 recessed flush mounted interior lights mounted in the driver's area of the bus (to the left and right of the centerline of the bus) operated by a separate control panel mounted switch. Lenses for all interior lights shall be Lexan™ or other polycarbonate material.

m. LICENSE PLATE LAMP

This lamp may be combined with one of the combination brake/tail lamps above.

n. MASTER SWITCH FOR BODY ELECTRICAL CIRCUITS AND OTHER SWITCHES

All bodies shall be equipped with an electrical circuit master switch that will turn body circuits ON and OFF by means of a solenoid (relay) controlled by the ignition switch. There shall also be a manual noise abatement switch installed in the control panel, labeled and alternately colored, and wired into the activation circuit for the master body circuit solenoid. This shall be an on/off type switch that deactivates all body equipment that produces noise, including, at least, the radio, heaters, air conditioners, fans, and defrosters. This switch shall not deactivate safety systems such as windshield wipers or lighting systems. On Type B, C, and D buses there shall also be a push-button switch or plug connector mounted in a location inaccessible to the driver to manually start the diesel particulate filter regeneration process. This switch or plug connector shall be appropriately labeled.

o. PUPIL WARNING LIGHTS, STOP ARMS, PUPIL CROSSING ARM, AND SYSTEM CONTROLS AND OPERATION

(1) Pupil Warning Lights

Pupil warning lights shall be dual mounted side by side on all corners of bus roof caps. Mounting shall be as high as practical on top and as near outer edge of bus as curvature permits. The lamps shall be securely mounted. Black background 1¼ inches to 3 inches wide shall be painted around lights. The lamps installed on outside shall be red; the lamps installed to the inside shall be amber. Lamps shall be clearly visible in bright sunlight for a minimum of 500 feet. Additionally, pupil warning lights shall:

- (a) Have light assemblies of a flat back design. Note: Cutouts in roof caps shall be no larger than necessary to accommodate pupil warning light wire. A flush-mounted design is acceptable.
- (b) Use replaceable quartz halogen bulbs.
- (c) Be 7 inches in diameter or 38 square inches minimum.

(2) System Controls- system must be equipped with the following driver actuated controls:

- (a) Master switch – provides means for deactivating entire system, as would be required when opening the door at a railroad grade crossing.
- (b) Control switch - 3 positions: **OFF, AMBER, and RED**. Switch may be rocker, pull-type, or other switch providing 3 positions. This switch shall be separated from the master switch by at least 1 inch, and shall be colored red.
- (c) Service door-actuated switch.
- (d) Controls must provide for the combinations of switch positions and conditions of pupil warning lights, stop arm(s), stop arm lights, and audible alarm as indicated on the chart below.

NOTE: System shall not be designed in such a way that the operator is required to actuate controls in a particular sequence to achieve the desired combination of conditions. EXAMPLE: If the driver places the three-position switch in the AMBER position, with the master switch ON, it must not be required that the three-position switch be moved to RED or that the service door be opened, in order to deactivate AMBER. In this example, the driver must be able to deactivate AMBER by going directly from the AMBER to the OFF position.

With Master Switch, Control Switch, and Service Door In The Following Positions:				Condition of Stop Arm(s), Stop Arm Lights, Amber and Red Pupil Warning Lights and Audible Alarm Must Be:				
	MASTER SWITCH POSITION (ON or OFF)	CONTROL SWITCH POSITION (three positions: off, amber, or red)	SERVICE DOOR POSITION		STOP ARMS, STOP ARM LIGHTS	AMBER PUPIL WARNING and PILOT LIGHTS	RED PUPIL WARNING and PILOT LIGHTS	AUDIBLE ALARM
1	ON	OFF	CLOSED	1	RETRACTED, OFF	OFF	OFF	OFF
2	ON	OFF	OPEN	2	RETRACTED, OFF	OFF	ON	ON
3	ON	AMBER	CLOSED	3	RETRACTED, OFF	ON	OFF	OFF
4	ON	AMBER	OPEN	4	RETRACTED OFF	OFF	ON	ON
5	ON	RED	CLOSED	5	EXTENDED, ON	OFF	ON	OFF
6	ON	RED	OPEN	6	EXTENDED, ON	OFF	ON	OFF
7	OFF	ANY POSITION	ANY POSITION	7	RETRACTED, OFF	OFF	OFF	OFF

(3) **Pupil Crossing Arm:** Required, meeting following:

- (a) Air operated on all air brake equipped buses. Electrically operated on all hydraulic brake buses.
- (b) Mounted to the far right side of the front bumper and shall open to an angle perpendicular to the bus.
- (c) All components and connections shall be weatherproofed.
- (d) Easily removable with hand tools for towing of the bus.
- (e) Shall meet or exceed SAE Standard J 1133.
- (f) Constructed of noncorrosive or nonferrous material or treated as per the body sheet metal standard.
- (g) No sharp edges or projections that could cause hazard or injury to students.
- (h) Four-point mounting to the front bumper.
- (i) The crossing arm shall extend approximately 72 inches from the front bumper when in the extended position, and shall be constructed of a yellow polycarbonate material or noncorrosive tubing painted yellow. Approximate dimensions of the arm shall be 65 inches X 3 inches X 1 inch.
- (j) Shall be extended simultaneously with stop arm(s) by means of stop arm control and shall retract within 8 seconds of deactivation.
- (k) Shall include a magnetic device or other assembly attached to the bumper at the end of the arm to provide a positive latch for the arm when not in use. This device shall also reduce the tendency of the arm to rattle and vibrate when not in use.
- (l) An electrically operated crossing arm may be used on air brake equipped buses only if it is a behind-the-bumper design and no air operated arm is available. This alternative must include a 5 year, 100 percent parts and labor warranty on the entire crossing arm assembly and requires prior approval of the Department.

(4) **Stop Arm Signals**

For all buses, 47 capacity and larger, there shall be installed on left outside of body 2 approved octagonal design stop-signal arms, each equipped with 2 double-faced alternately flashing strobe-type lights for signaling a pupil stop. All buses of less than 47 capacity shall be equipped with 1 stop arm as described. Bodies to be mounted on diesel powered chassis with hydraulic brakes shall be equipped with electrically actuated stop arm(s). Air powered stop arms shall be standard on all air brake equipped buses. Rear stop arm location on dual stop arm equipped buses shall be on left side of bus, as close as is practical to left rear corner of body. Light lens of all stop arms shall be RED. Air lines must not be readily accessible to students inside or outside the vehicle.

Air lines must be made of copper, steel, or nonmetallic materials meeting SAE Standard J848d, and fittings shall be brass. Stop signal arms shall meet the applicable requirements of SAE J1133. For controls, see above item. Stop arms shall retract within 6 seconds of deactivation. For color, see **LETTERING AND TRIM, page III-15.**

p. **REFLECTORS**

2 amber reflectors shall be mounted on the sides of the bus body near front even if chassis incorporates amber reflectors at or near the front of the chassis cowl area, and 2 red on rear side panels, 2 red on rear panels, and 2 intermediate amber on buses over 30 feet.

q. **STEP WELL LIGHT**

Step well light shall illuminate the bus entrance and be adequately protected. Step well light shall be activated automatically when door is opened and clearance lights are on. Clearance lights shall be activated by headlight switch when the ignition switch is on. See **SERVICE DOOR, page III-19,** for further operational requirements.

r. **STROBE LIGHT, WHITE FLASHING**

Each bus shall be equipped with a white flashing strobe light meeting the following requirements (also see **WARRANTIES, page 12:**

- (1) Shall have self-contained power supply.
- (2) Construction: Base shall be Lexan™ or other polycarbonate or corrosion resistant metallic material. Lens shall be clear Lexan™ or other polycarbonate material of equal or better strength, resilience, and durability. Unit shall be sealed to protect against intrusion of dust and moisture. All external fasteners including mounting screws shall be stainless steel or coated using the dacromat or magnagard process. Unit shall have mounting gasket to isolate the light assembly from vibration.
- (3) Electrical characteristics: Shall have a flash energy of 8 joules minimum. Shall have 80 (plus or minus 10) single or double flashes per minute. Shall have integral fuse or circuit breaker protection and reverse polarity protection. Maximum current draw shall be 2 amperes at 12 volts.
- (4) Dimensions and location: Overall height of unit shall be approximately 4 inches to 6 inches, with lens diameter approximately 4 inches to 6 inches. Mounting location is to be centered (laterally) on roof of bus, approximately 48 inches (longitudinally) from rear edge of rear roof cap.
- (5) SAE Specifications: Shall meet SAE J575 and J1318.
- (6) Body circuitry: Shall include a separate, clearly labeled driver's panel mounted switch, with a clearly labeled pilot light.

s. **TURN SIGNAL LAMPS**

Front turn signal lamps shall be furnished by chassis manufacturer on Type A1, A2, B, and C buses. If turn signal lights are not built into the front end assembly, front turn signals must be added by the body builder. Front turn signal lamps on Type D bodies shall be the same as the rear turn signals, unless the turn signals are incorporated as part of the headlight assemblies or otherwise incorporated into the front end design as approved by the Department. Lenses of rear turn signal lights shall be amber in color, 7 inches in diameter or 38 square inches minimum, Class A, mounted as far apart laterally as practical on the same horizontal centerline as the large brake/tail lamps. All buses shall also be equipped with an amber turn signal light in a protective rim on each side of the bus (same light as used for clearance lights), mounted rearward of the service door on the right side and rearward of the front stop arm on the left side. All buses over 30 feet in length shall have 2 turn signal lights (same light as used for clearance lights) mounted in protective rims on each side of the bus. The rearmost side turn signals on buses over 30 feet shall be mounted at or rearward of the centerline of the rear axle.

Rear turn signal lights shall:

- (1) Be LED type lights.
- (2) Use a universal type sealed plug connector.
- (3) Meet current SAE requirements and be installed in compliance with Federal Motor Vehicle Safety Standards.
- (4) Be 7 inch diameter or at least 38 square inches.

t. **TWO-WAY RADIO**

Use of a school district-approved two-way radio communications system is acceptable.

u. **VIDEO CAMERA MONITORING SYSTEMS**

Districts may install video cameras in buses provided the system:

- (1) Is installed securely in an area at the front of the bus.
- (2) Is outside the federal head impact zone (FMVSS 222).
- (3) Is located in an area not likely to cause student injury.
- (4) Has no sharp edges or projections.

8. **EMERGENCY EXITS**

- a. Emergency door on all Type A, B, C, and front engine Type D buses shall be located at center of rear of bus and have minimum horizontal opening of 24 inches and vertical opening of 48 inches. Emergency door shall be hinged on right-hand side using hinge(s) with a brass or rust resistant rod. Doorstop and hold-open device shall meet the requirements of the National School Transportation Specifications & Procedures, Revised 2005, Emergency Exits. Inside of door header shall be padded with energy absorbing material a minimum of 3 inches wide.
- b. The emergency door shall be designed to open from inside and outside of bus and shall have a fastening device, which may be quickly released but designed for protection against accidental release. Control from driver's seat shall not be permitted. Outside control shall consist of nondetachable opening device designed to prevent "hitching to," but to permit opening when necessary.
- c. Emergency door shall be equipped with slide bar, cam-operated latching device, having a minimum stroke of 1 inch. Emergency door latch shall be equipped with suitable electric plunger type switch connected with buzzers as required by FMVSS. Switch shall be enclosed in a metal case or durable case of other material, with rounded, protected edges. Wires leading from switch shall be concealed in bus body. Switch shall be installed so that plunger contacts farthest edge of slide bar in such a manner that any movement of slide bar will immediately close switch circuit and activate buzzer. Door latch shall be equipped with interior handle that extends approximately to center of emergency door. It shall lift up to release.
- d. Emergency door controls, labeling, and warning device shall meet requirements of FMVSS 217. There shall also be attached to the door, in such a way that it is visible inside and outside the bus, labeling as follows: "This door is equipped with a hold-open device. To release, open the door to its fully opened position." This sticker shall be red on a white background and lettering shall be a minimum of ½ inch.
- e. Each bus shall also be equipped with push-out type emergency exit side windows that comply with FMVSS 217 and National School Transportation Specifications and Procedures, Revised 2005, when used with the roof hatch(es) specified below. These windows shall be of similar design to standard side windows, except for the following:
 - (1) Window assembly shall be hinged on the forward side and include a latching device for securing in the normal (non-emergency) position and to allow emergency opening.
 - (2) Each window shall be equipped with a switch to activate a buzzer when the emergency opening latch is released.
 - (3) The lettering "EMERGENCY EXIT" shall be located on or above the window, inside and outside the bus.
 - (4) Shall not be placed next to any of the forward-most seats required to be spaced at 28.5 inches of knee room.
 - (5) Emergency windows shall be installed in the following numbers on standard buses:

0 to 40 capacity	1 window per side
41 to 72 capacity	2 windows per side
73 to 90 capacity	3 windows per side
 - (6) Wheelchair lift equipped buses shall have the minimum number of emergency exit windows required by FMVSS # 217.

- f. Buses 35 capacity and smaller shall be equipped with 1 roof hatch-type emergency exit/ventilator. Buses over 35 capacity shall be equipped with 2 roof hatch-type emergency exit/ventilators. Specifications for roof hatch(es) shall be as follows (also see **WARRANTIES, page 12**):
 - (1) Shall comply with all requirements of FMVSS 217 for emergency exits.
 - (2) Hinge(s) shall be located on forward and rearward side of hatch.
 - (3) Shall be equipped with an outside release to allow opening emergency exit from outside bus.
 - (4) Shall be labeled "Emergency Exit" inside and outside and shall be labeled with instructions for release inside and outside.
 - (5) Shall provide a "partially open" position along full width of hatch adequate to allow air to enter or exit and thereby ventilate bus by opening either the front or rear of the hatch. Hatch shall allow for partial opening on any of its 4 sides and on all 4 sides simultaneously.
- g. All school bus bodies built under these specifications shall meet the requirements of FMVSS 217 and National School Transportation Specifications & Procedures, Revised 2005, related to emergency exits.

9. EMERGENCY ROADSIDE REFLECTORS

There shall be 3 reflector-type warning devices, meeting the requirements of FMVSS 125, mounted in a location accessible to driver in front section of bus and stored in a container. The container shall be sealed with a breakable, nonreusable seal.

10. FIRE EXTINGUISHER

- a. A dry chemical-type fire extinguisher with a gauge and designed to restrain tampering shall be mounted in a place accessible to driver, preferably near service door.
- b. Fire extinguisher shall bear the label of Underwriters' Laboratories, Inc., showing a rating of no less than 2A-10BC.

11. FIRST-AID KIT

- a. Bus shall carry a Grade A, moisture and dust proof, first-aid kit with clear cover, mounted in such a manner that it can be easily detached and made portable and in an accessible place in driver's compartment. The container shall be sealed with a breakable, nonreusable seal.
- b. Number of units and contents shall be as follows:

1 inch bandage compress (e.g., Band-Aids)	2 packages
40 inch triangular bandage with 2 safety pins	1 package
4 inch X 4 inch sterile gauze pads	2 packages of 6 each
Rolled curlex bandage each in length.....	2 inches X 6 yards
1 inch roll adhesive tape in length.....	1 roll 2½ yards
Eye dressing packet.....	2 packages

12. FLOOR AND FLOOR COVERING

- a. Floor shall be of prime commercial quality steel of at least 14-gauge thickness or other metal at least equivalent in strength to 14-gauge steel. Floor shall be level from front to back and from side to side except for wheel housings, toeboard, and driver's seat platform areas.
- b. (1) Floor Sills - There shall be one main body sill at each side post and two intermediate body sills on approximately 10 inch centers. All sills shall be of equal height not to exceed 3 inches. All sills shall extend the width of body floor except where structural members or features restrict area. Main body sill shall be equivalent to or heavier than 10 gauge and each intermediate sill shall be equivalent to or greater than 16 gauge, or each of all body sills shall be equivalent to or heavier than 14 gauge. All sills shall be permanently attached to floor.

- (2) Connections between sides and floor system shall be capable of distributing loads from vertical posts to all floor sills.
- c. Driver's compartment plate on conventional body shall be removable, installed on level with bus floor. All components requiring servicing must be readily accessible. Openings in bus floor to meet this requirement shall be reinforced to maintain full strength of unpunctured floor.
- d. Body floor shall have an access hole for removal and repair of fuel tank sending unit.
- e. All Type B, C, and D body manufacturers shall provide an access cover in the body floor adequate to allow removal of the fuel pump without lowering the fuel tank. This requirement applies to all chassis equipped with an in-tank electric fuel pump.

NOTE: Items a-e above do not apply to Type A1. For Type A1 the floor shall provide adequate and firm support for seat legs and shall have a minimum 1/2 inch pressure-treated plywood securely attached to floor. Plywood shall be all veneer APA rated sheathing marked "EXPI" or "EXT". Preservative treatment shall be minimum 0.40 pounds of chromated copper arsenate per cubic foot of plywood. Marine grade plywood may be supplied as an alternative if approved by the Department of Education. Basic floor construction of Type A1 buses shall be manufacturer's standard, meeting applicable FMVSS.

- f. Floor in under-seat area, including tops of wheel housings and toeboard, shall be covered with smooth surfaced elastomer covering, or approved equal, having a minimum thickness of 0.125 inch. Floor covering shall be flame-resistant and shall have a rating of SE/NBR (self-extinguishing/no burn rate) when tested in accordance with FMVSS 302. Floor covering shall be ultra-violet, ozone, and moisture-resistant and have a minimum tensile strength of 1200 psi and a minimum elongation of 100 percent. Floor covering shall be abrasion-resistant and slip-resistant and have a minimum coefficient of friction of 0.85 as measured under ASTM D 1894 or 0.65 as measured under ASTM D 2047.
- g. Covering from top step landing area to emergency door (or rear seat on Type D rear engine buses) shall be ribbed aisle-type non-skid, wear-resistant fire-resistant elastomer,. Minimum overall thickness shall be 0.1875 inch measured from top of ribs. Elastomer floor covering shall meet Federal Specification ZZ-M-71d.
- h. Floor covering must be permanently bonded to floor and resist cracking when subjected to sudden changes in temperature. Adhesive material used shall be waterproof and of the type recommended by manufacturer of floor covering material.
- i. Landing area at top of steps shall be ribbed elastomer, which shall extend to the ribbed aisle floor cover. The leading horizontal edge, or nosing, shall be white or yellow ribbed elastomer or other contrasting color and shall have an integral 90 degree turn down with a square leading edge matching the step treads.
- j. All joints or seams in the floor covering shall be covered with non-ferrous metal, minimum 1 inch wide and .095 inch thick, weight .09 per linear foot, providing driver's compartment, except at cowl, shall have a special approved molding. Alternate materials may be used if they provide equivalent durability to the above requirement. Molding shall be securely attached to prevent a tripping hazard.
- k. Manufacturers may use seamless one-piece floor rubber with integral ribbed aisle in any bus meeting the above requirements. Aisle molding is not required with one-piece flooring.
- l. All holes in the chassis firewall and around transmission cover and engine housing shall be adequately sealed.
- m. Districts may replace the above-required flooring material with a commercially available truck bed liner material having equivalent or better physical properties to the required flooring material.

13. FUEL FILLER OPENING

An opening of adequate size and design shall be provided over fuel filler. Also see **LETTERING AND TRIM, page III-15.**

14. GRAB HANDLE AT ENTRANCE

A suitable grab handle or rail shall be provided at the front entrance, securely mounted inside of body. Grab handles shall be made of round stainless steel, 1 inch OD, tubing minimum of 18 gauge or stainless architectural tubing minimum 0.018 inch thickness over 18 gauge steel insert. Grab handle and mounting shall be designed to minimize the possibility of students' clothing or personal items becoming lodged or caught upon exiting the bus, in order to reduce the risk of injury or fatality to passengers from being dragged outside the bus.

HEATER / DEFROSTER

See ELECTRICAL EQUIPMENT AND WIRING, page III-5.

15. INSPECTION

Purchase of school buses or bus bodies under this specification shall include the right to inspection of the product before, during, and after manufacture by any appropriate state agency or county agency of the State of Florida.

16. INSULATION AND SEALING OF JOINTS

- a. Thermal insulation material, if provided, shall be of a type that will not harbor dampness, is fire-resistant, and is approved by Underwriter's Laboratories, Inc.
- b. Overlapping of edge of exterior roof and side panels and also the top edge of rub rails shall be sealed to prevent moisture, dust, and other contaminants from entering the joint and the bus.

17. LETTERING AND TRIM

Trim on 3 rub rails below beltline and all lettering shall be black (except for stop signs). Entrance door frames, pilaster panels, and other trim panels may be painted black if approved by the Department. Letters of words "SCHOOL BUS" on top front and rear section of bus body shall be 8 inches high and correspond to Series B, Standard Alphabet (see National School Transportation Specifications & Procedures). "(Name of District) DISTRICT SCHOOLS," on each side of bus body at beltline shall be in 6 inch minimum letters. Private and charter schools may alternately affix the name of the school in the aforementioned format and location. Numbers shall be in 6 inch minimum height and on each side and on front bumper and rear of bus body. "EMERGENCY DOOR" shall be in 2 inch letters at top or directly above door, visible inside and outside of bus. Lettering to indicate fuel type shall be located on body adjacent to fuel filler opening using minimum 1 inch letters. The words "STOP WHEN RED LIGHTS FLASH" shall be displayed on the back of all buses in 6 inch black letters. Also see lettering requirements for roof hatches and push-out windows under EMERGENCY EXITS, page III-12. Districts may add an American flag decal to the exterior of the bus. If used it shall be no more than 6 inches x 10 inches and be located in front of the district name on the beltline of the bus. Also see United States Public Law 4USC7.

Front stop signal arm (both sides of arm) and rear stop arm (rear side only) shall have red background with a reflectorized white border and the letters "STOP" shall be in 6 inch white reflectorized letters. Both sides of the front stop arms and the rear side of the rear stop arm shall have reflectorized red sheeting of high intensity-type material. Material shall be warranted for 10 years against cracking, delamination, bubbles, wrinkles, or significant color changes (such as fading of red background); warranty shall include full replacement of material (not including labor). The front side of the rear stop arm shall be painted red. Also see WARRANTIES, page 12.

NOTE: Buses shall include the lettering and trim specified above, and may include, but shall be limited to, lettering, trim, symbols, markings, and coloration specified in the National School Transportation Specifications and Procedures, Revised 2005.

18. LICENSE HOLDER

License holder shall be on left rear outside of body with suitable method for mounting license tag.

19. LOCKUP DEVICES

Any emergency door equipped with a locking device shall have an ignition interlock, which prevents starting the engine when the door is locked and shall meet requirements of FMVSS 217. Emergency exit windows shall not be operable (under normal conditions) from outside the bus and shall not be equipped with any locking device.

20. MIRROR SYSTEM

- a. **Interior Mirror:** Shall provide adequate viewing of the entire length and width of the interior of the bus and be at least 6 inches X 30 inches. Mirror shall include the following characteristics:
 - (1) Shall utilize a 1/8 inch thick tempered safety glass mirror lens that meets or exceeds ANSI Z97.1 requirements for safety glazing in mobile environments and is bonded to the mirror housing.
 - (2) Shall include a heavy-duty, single-piece mounting bracket that fastens both to the front and bottom of the header panel in order to ensure stability.

- (3) Housing shall be constructed of aluminum and shall be powder-coated, low-gloss black.
- (4) Shall incorporate a single knob (thumbwheel) adjustment to allow the driver to reposition the mirror without the use of tools.
- (5) Shall have a soft gasket type frame that is bonded to the housing.

NOTE: Interior mirror on Type A1 shall be a minimum of 50 square inches and meet the above requirements.

- b. **Exterior Mirrors:** Each school bus shall be equipped with a system of exterior mirrors complying with FMVSS 111 and meeting the following requirements:
 - (1) Cross/Side-View Mirror System: The cross/side-view mirror system shall provide the driver with indirect vision of an area at ground level from the front bumper forward, and the entire width of the bus, to a point where the driver can see by direct vision. The system shall also provide the driver with indirect vision of the area at ground level around the left and right front corners of the bus to include the tires and service entrance on all types of buses to a point where it overlaps with the rear vision mirror system. This mirror system shall incorporate the following features or requirements:
 - (a) Only one mirror shall be installed at each front corner of the bus.
 - (b) Mirrors shall not reflect excessive glare from the bus headlights or the sun into driver's eyes. Mirrors shall be a $\frac{1}{4}$ sphere or shaded $\frac{1}{2}$ sphere design.
 - (c) Stainless steel fasteners or fasteners coated using the dacromat or magnagard process shall be used in the construction of the mirror, mounting brackets, and to hold the brackets to the body.
 - (d) Mirror stabilizer brackets on all Type B and C composite hoods shall use through-the-fender rubber or nylon mounts with stainless steel caps to reduce mirror vibration and erosion of the hood material.
 - (2) Rear Vision Mirror System: A rear vision mirror system shall be provided that incorporates the following features and requirements:
 - (a) System shall consist of 1 aerodynamic mirror head, containing 1 flat and 1 convex mirror lens per side. Each mirror set shall be mounted on a single breakaway arm with positive detent or lock. The arm shall be mounted such that it holds the mirror from the top when possible. Type A1 buses may be exempted from this requirement if no such bracketry is available.
 - (b) Each of the 4 required mirrors in the rear vision mirror system shall be electrically operated, remote-control rear view mirrors.
 - (c) For Type A2, B, C, and D buses, the convex mirrors shall have a minimum of 38 square inches and the flat rear view mirrors shall have a minimum of 61 square inches of mirror surface. For Type A1 buses, the convex mirrors shall have a minimum 28 square inches and flat rear view mirrors shall have a minimum of 61 square inches of mirror surface.
 - (d) Stainless steel fasteners or fasteners coated using the dacromat or magnagard process shall be used in the construction of the mirror, mounting brackets, and to hold the brackets to the body.
 - (3) Overall exterior mirror system (cross/side-view and rear vision mirrors) shall incorporate the following features and requirements:
 - (a) Mirrors shall be isolated from vibration.
 - (b) Certification of compliance of the system with FMVSS 111 shall be provided as required by the Department of Education. Also see **WARRANTIES, page 12.**

21. PAINT AND FINISH

- a. Prior to the application of the finish coats to body, hood, and cowl, all surfaces shall be cleaned of grease, foreign matter, excessive body caulking, and sealing material and treated as per paint manufacturer's recommendation for proper paint adhesion.

National School Bus Yellow paint shall meet National School Transportation Specifications & Procedures for color and shall have a finished gloss rating of at least 85 at 60°F and a distinctness of image rating of an average of at least 50 measured using the same method specified for gloss under **WARRANTIES, page 12**. Paint shall be applied for a total dry thickness of at least 1.8 mils over all painted surfaces. School bus roofs shall be painted white in color, and shall meet the above gloss and DOI ratings. White paint may extend to the leading and trailing edge of the roof caps, and may extend down to the drip rails. Trim, lettering, and bumpers shall be black except that bumpers may be striped in accordance with National School Transportation Specifications & Procedures or these specifications. Lead-free paint shall be used on all interior and exterior surfaces of the body and chassis. Also see **WARRANTIES, page 12** for warranty requirements, **STRUCTURAL DESIGN, page III-20** for required metal preparation, **LETTERING AND TRIM, page III-15**, and **REFLECTIVE MARKINGS, page III-17**.

b. The interior of the bus body shall be painted with light gray paint meeting the following color specifications:

$L^* = 77.37$
 $a^* = - 1.17$
 $b^* = - 0.69$

22. PANELING, EXTERIOR

- a. Exterior paneling includes all sheet metal skin forming exterior surface of body.
- b. Exterior paneling should be of 20 gauge steel minimum thickness and shall be attached to bow frames and strainers to act as an integral part of structural frame. All joints shall be designed and constructed to provide maximum structural integrity and elimination of water and dust intrusion. There shall be no sharp edges that could cause injury to persons around the outside of the bus.

All joints of roof panels shall be lapped the full width of supporting members and shall be attached along each side of supporting member to form a watertight joint. Also see **STRUCTURAL DESIGN, page III-20**, and **INSULATION AND SEALING OF JOINTS, page I-7**.

23. PANELING, INTERIOR

- a. Interior of body shall be lined with panels securely fastened to adjoining parts in an acceptable manner. If ceiling is constructed so as to contain lapped joints, exposed edges shall be beaded, hemmed, flanged, or treated to minimize sharp edges. Fastenings shall minimize vibrations and rumble and be installed to facilitate removal. A cove molding, which may be an extension of body panels, shall be installed covering wall to floor joint beginning at windshield post on left side of bus and extending along walls around corners to service door on right side. Molding shall be securely fastened so that dirt will not readily work under it.
- b. Interior paneled area immediately below window line shall be aluminum-coated steel. Exposed edges of interior paneling shall be beaded, hemmed, flanged, or treated to eliminate sharp edges.

24. PUBLICATIONS

Each Florida school board that is delivered one or more bus bodies shall be furnished a parts catalog and a parts price list. Parts manuals must be designed so that all replaceable parts are illustrated by line drawings and such parts are numbered on the illustration, with a part description on a separate list under the corresponding number. Part descriptions should be annotated appropriately with the part number, a proper description (part name), and the quantity required for the application illustrated on the drawing.

PUPIL WARNING LIGHTS AND PUPIL CROSSING ARM

See **ELECTRICAL EQUIPMENT AND WIRING, page III-5**.

25. REFLECTIVE MARKING PACKAGE

There shall be installed a reflective marking package as specified in the National School Transportation Specifications & Procedures, Revised 2005. This package shall include markings for the front, rear, both sides, and front and rear bumpers. Striping on sides of bus shall be 2 inches wide meeting the ASTM D-4956-90 Type 5 reflective sheeting standard. Front and rear bumper striping shall cover as much of the height and width of the bumper as is practical, and shall be at least 8 inches in height. Striping shall be installed longitudinally the length of the body at the vertical location immediately below the seat level rub rails but high enough so as to clear wheel wells, whenever possible. Short breaks in the striping at rivet locations are acceptable. Reflective markings are also required for all emergency exits as specified in FMVSS 217.

26. **RUB RAILS**

- a. There shall be a rub rail on each side of bus approximately at seat level, which shall extend from entrance doorpost around bus body (except for emergency door) to point of curvature near cowl on left side.
- b. There shall be rub rails located approximately at the floor line, and the bottom of outer skirt, which shall cover the same longitudinal area as upper rub rail, except at wheel housings, and shall extend only to radii of right and left corners.
- c. Rub rails shall be attached twice at each body post and at all other upright structural members.
- d. Rub rails shall be 4 inches or more in width, shall be of 16 gauge steel, and shall be constructed in corrugated or ribbed fashion.
- e. Rub rails shall be applied outside of body panels. Pressed-in or snap-in rub rails do not satisfy this requirement.

27. **SEATING, MODESTY PANELS (CRASH BARRIERS), LAP BELTS, AND WEBBING CUTTERS**

- a. Seats shall be mounted forward-facing and provide a minimum of 12.8 inches of seat width per passenger seating position. The aisle shall be 12 inches minimum. This plan of body seating shall determine seating capacity.
- b. Seat spacing shall meet the requirements of Federal Motor Vehicle Safety Standard 222. The first 3 seats on each side of all Type B, C, and D buses, and the first seat on each side of all Type A buses shall be spaced at 28.5 inches of knee room. The rest of the passenger seats shall provide for a minimum of 25 inches knee room at each seat with a measurement to be made at the center of the reference point. In making this measurement from back of seat cushion to back of seat or barrier in front, upholstery may be placed against padding both forward and rear, but padding may not be compressed. All 39 inch seats set at 28.5 inches seat spacing shall be equipped with two sets of FMVSS 225-compliant child safety seat anchorage points per bench seat. All seats set at 28.5 inches of seat spacing with a seat width of less than 36 inches shall be equipped with one set of FMVSS 225-compliant child safety seat anchorage points per bench seat.

NOTE: Type C and D school bus bodies over 39 feet in length may provide for a minimum of 24 inches knee room in seats behind the third row.

- c. All passenger seats shall be of the high back design; i.e., 24 inches above the seating reference point.
- d. All passenger seat bottoms shall be securely attached to the seat frame with devices that allow the seat bottom to pivot forward without becoming detached from the frame. This device shall be constructed of a gauge of metal that resists deformation. The seat bottom shall also have a latch at the rear that is operable without tools. These devices shall have rounded or protected edges.
- e. Seat padding shall be secured to the frame so that it will not snag. Screws and bolts used in seat back construction shall not be exposed.
- f. Modesty panels and passenger seats, including seat back and entire bottom cushion (including underside), shall be covered with vinyl-coated material. All passenger seat assemblies and modesty panels shall meet the requirements of the 2005 National School Transportation Specifications & Procedures, School Bus Seat Upholstery Fire Block Test. Upholstery material for all passenger seats and barriers shall meet the following color standard +/- four delta E:

	<u>III/ob</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>x</u>	<u>y</u>
1	D65 Daylight	7.21	7.92	12.52	2606	2963
2	2	7.51	7.30	4.07	3978	3865
3	Rom Light	7.33	7.37	8.15	3207	3226

- g. Buses shall have an FMVSS type padded barrier in front of the forwardmost passenger seat on each side of the bus. Also see Section V for barrier requirements for wheelchair lift equipped buses. Modesty panels at entrance side and driver's side shall have a full-width, aluminized steel panel below the padded section extending down to the floor, except as specified under heater/defroster specifications (see **ELECTRICAL EQUIPMENT AND WIRING, page III-5**).
- h. **All Type A school buses sold through the State Bid for School Buses shall be equipped with Type II, 3 point seat belts in all passenger seating positions. These belt systems shall meet the requirements of National School Transportation Specifications and Procedures, Revised 2005.**

- i. If required by Florida Statutes, all Type B, C, and D buses shall be equipped with lap belts in all passenger seating positions, meeting the following requirements:
 - (1) All belts and anchorages must comply with FMVSS 209 and 210.
 - (2) Belts shall be manufacturer’s standard style lap belts. The nonadjustable buckle end of each belt shall be the aisle-side connection point on each passenger seat.
 - (3) Each two-part belt shall be separately color-coded to aid in proper connection.
 - (4) The nonadjustable buckle end of the belt shall extend from the seat bight at least 12 inches, and the male end shall extend at least 38 inches.
 - (5) Any belt system with parts that can be manually disassembled without the use of tools and any system that is subject to easy vandalism shall not be approved for use in Florida school buses.
 - (6) Retractable seat belts are permissible at the purchaser’s option. If this system is specified, the retractors shall be emergency locking type, and the retractors must be mounted below the seat bight.
 - (7) All federal requirements shall supercede any of these requirements that are in conflict.
 - (8) School districts may install restraining systems that differ from these requirements as necessary to accommodate pre-school age children and children with special needs. Such systems shall comply with FMVSS 209, 210, and 213 as applicable, and shall be approved by the body manufacturer.
- j. All buses shall also be equipped with a durable webbing cutter having a full width handgrip and a protected, replaceable blade. The required belt cutter shall be mounted in a location accessible only to the driver in the seated position, and be easily detachable.

28 SERVICE DOOR

- a. Service door shall be a split type or jackknife type located at right front of bus. Doors shall be securely hinged with approved heavy-duty hinges with brass or rust resistant rod adequately fastened to adjoined member. Doors shall have a 1 1/2 inch minimum safety gap sealed with a safety flap of approved quality. Door shall extend to bottom step and be fitted with suitable weather strip to restrain water entering step well.
- b. An air operated entrance door shall be provided on all air brake equipped buses. This system shall have a manually operated override to enable the driver to manually open the door in the event of loss of power. Air powered entrance doors shall operate in accordance with the following table:

Ignition Switch Position	Door Switch Position	Emergency Dump Switch Position	Door Position / Status	Step Well Light Condition
Off	Any	On	Neutral	Off
Off	Any	Off	Neutral	Off
On	Closed	Off	Closed/Active	Off
On	Opened	Off	Open/Active	On
On	Closed	On	Neutral	Off
On	Opened	On	Neutral	On

Additionally, when the key switch is in the “off” position, this system must not create a battery draw. All air door systems must provide a rebuildable air cylinder and must operate reliably in all weather and temperature conditions. All air powered door systems must include a method of manually adjusting the opening and closing speed and force of the doors.

- c. Hydraulic brake buses shall have a manually controlled entrance door. A double-bearing, epoxy-coated, mechanical control shall be mounted within comfortable reach of driver on a firm and substantial support and lock in off-center position. On models with service doors opening outward, there shall be installed an approved safety latch. Control shall have a smooth machined handle and the rod to the door shall be epoxy-coated.
- d. Service door shall have a minimum horizontal opening of 24 inches and a minimum vertical opening of 68 inches. Immediately above the door opening there shall be secured to body panel a high-density foam rubber pad, a minimum of 3 inches in width, or approved equal safety cushion.

- e. Doors shall be designed and weather strips mounted so that there is no binding or tendency for stripping to dislodge during door operation. 1 or 2 glassed-in openings shall be provided in each door half with glass of same grade as specified on side windows and mounted in rubber. Bottom of lower glass panel shall not be more than 30 inches from ground when bus is unloaded. Top of upper glass panel shall not be more than 6 inches from top of door.

29. SIZES OF BODIES

The maximum overall length of any bus shall be 45 feet; maximum overall outside width of all bodies shall be 102 inches. Height of body from top of finished floor to underside of ceiling, at center of body, shall be a minimum of 72 inches.

30. STEP WELL

A step well of at least 3 steps shall be built in the right front assembly enclosed with doors extending to bottom step. Each step shall be covered with abrasion resistant "Pebble-Top" type elastomer, the base of which shall be at least 3/16 inches thick, with an overall thickness of 5/16 inch bonded to durable polymer base and otherwise constructed to provide substantial support, including the leading horizontal edge, which shall be "Pebble-Top" type, and white or a color that contrasts with the step tread by at least 70 percent. The polymer backing shall have an integral 90-degree turn-down with a square leading edge for slip resistance. The lower (first) step height shall be between 10 and 14 inches above the ground for all Type A1, A2, B, and C buses. Type D buses shall have a first step height 12 to 16 inches from the ground. Each step must be the full width of the step well at the point where the step is located. **Half steps or partial steps are not acceptable.**

NOTE: Two steps acceptable on Type A1 buses.

STOP ARMS

See **ELECTRICAL EQUIPMENT AND WIRING, page III-5.**

31. STRUCTURAL DESIGN

- a. Details of design shall have a direct relationship to specifications for grades of steel in the latest edition for the design of Light Grade Cold-Formed Steel Structural Members of the American Iron and Steel Institute. Material used in the body frame structure shall conform to chemical and mechanical requirements of the listed specifications or other published specifications, including tensile and yield points, which establish properties and suitability of the steel for school bus body test code and safety requirements. All Type A, B, C, and D bodies shall meet the requirements of FMVSS 221 and the requirements of the 2005 National School Transportation Specifications & Procedures, Side Intrusion Test.
- b. All welds used in construction of body shall conform to latest applicable specifications of the American Welding Society.
- c. Welds, rivets, or high-strength bolts may be used in connecting parts of the structural body. Additional methods of body construction, such as structural adhesive, may be approved at the discretion of the Department. All bolts shall have provision to prevent loosening under vibratory loads. All bolts, nuts, washers, and screws used throughout the body shall be cadmium or zinc plated, or thoroughly treated in an approved manner for prevention of rust.
- d. All metal used in construction of bus body shall be zinc or aluminum coated before construction, and for metals 12 gauge or less in thickness, either zinc or aluminum coating shall be mill-applied for these components: (a) service door panels, (b) emergency door panels, (c) guard rails, (d) all exterior body panels, (e) wheelhousings, (f) body posts and roof bows, (g) side strainers, (h) roof strainers, (i) window caps, (j) window visors where used, (k) all floor section panels and floor sills. Door handles, interior decorative parts, and other interior plated parts are excluded. All metal parts that will be painted shall be chemically cleaned, etched, zinc-phosphate-coated, and zinc-chromate or epoxy-primed, or conditioned by equivalent process. Any areas from which primer is removed for any purpose, such as sanding, grinding, welds, etc., must be thoroughly cleaned and treated as specified and primer must be applied. Rivets used in assembly shall be zinc-phosphate treated unless coated with rust prevention material and primed as specified. In providing for these requirements, particular attention shall be given to lapped surfaces, welded connections or structural members, cut edges, metal in which holes are punched or drilled, closed or box sections not vented or drained, and surfaces subjected to abrasion during vehicle operation.
- e. As evidence that above requirements have been met, samples of materials used in construction of the bus body, when subjected to 1,000 hour salt spray test as provided for in latest revision of ASTM, Designation: B 117, "Standard Method of Salt Spray (Fog) Testing," shall not lose, after rubbing to remove corrosion, more than 10 percent of material by weight.

- f. The front end assembly shall be sufficiently heavy to withstand vibrations transmitted to it through chassis cowl. Windshield or corner posts must be of sturdy construction, designed so that they will not be so wide as to unnecessarily obstruct driver's view. Body shall be fastened to chassis cowl in an approved waterproof manner.
- g. All bus bodies shall be constructed to be in square, and level. There shall be no more than 1 inch of difference from side to side at the front and rear of the bus body (not counting any chassis lean or twist). All bodies shall be mounted such that all designed body contact points are in contact with the chassis frame. All bodies shall be centered on the chassis but shall be no more than 1/2 inch off of dead center.

NOTE: Type A1 buses may be constructed with exterior paneling and roof caps of material other than steel, meeting all body manufacturer requirements and applicable FMVSS. Body structural design shall comply with all other applicable requirements above.

32. SUN SHIELD

A dual sun shield system shall be provided, consisting of two independently mounted sun shields. One shall be mounted above the windshield and the other above the driver's window. Each visor shall have a tinted Plexiglass sun shield, minimum 6 inches X 24 inches, and have rounded bull-nosed perimeter edges and radius corners.

NOTE: Manufacturer's standard sun visor acceptable on Type A1 buses.

33. TAILPIPE

For all Type A, B, C, and D buses, the body manufacturer shall install a tailpipe or extension that extends beyond the exterior surface of the rear bumper, but no more than 2 inches beyond it. There shall be no sharp or jagged edges at the end of the pipe.

34. TESTING OF BODY

Load test of body shall meet the requirements of Federal Motor Vehicle Safety Standard 220.

35. UNDERCOATING

Entire underside of body including floor members, wheelhousings, and side panels below floor level shall be coated with fire-resistant asphalt base, rubber base, or other undercoating material, applied by spray method to seal, deaden sound, insulate, and prevent oxidation. Any undercoating material used shall be asbestos-free.

36. VANDAL BOX, SIDE MOUNTED

There shall be installed on all Type B, C, and D buses an equipment compartment on the ceiling above the driver's side window, measuring approximately 33" X 10" X 9" or providing equivalent space to the aforementioned size compartment. The compartment shall have a door with a positive latch and a keyed-alike lock with warning buzzer to warn the driver that the door is locked if the ignition switch is turned on.

37. VENTILATION

Body shall be equipped with an effective exhaust type ventilation system, noncloseable type installed in low pressure area of roof, capable of ejecting foul air under all operating conditions. System shall be adequately weatherproof and dustproof.

38. WARRANTIES

Bids submitted under this specification shall include a warranty covering materials and workmanship for a period of at least 1 year. See component warranties under **Warranties, page 12.**

39. WHEEL HOUSINGS

Wheel housings shall be constructed of 18 gauge or heavier steel and be rigidly reinforced, shall be attached to floor and side panels in such manner as to prevent water or dust from entering body, and shall be designed for easy removal of tires. For materials, see STRUCTURAL DESIGN, page III-20; for covering, see FLOOR AND FLOOR COVERING, page III-13.

40. WINDOWS

- a. Tinted glass that provides maximum tinting allowed by federal and ANSI standards for the windshield, driver's side window(s), and service door glass and that also includes tinted glass in all windows rear of the driver's compartment with a light transmission of approximately 28 percent shall be required on all Type A, B, C, and D school buses.
- b. An adjustable split sash window shall be mounted in side of bus body between each framing post. Safety glass shall be set in an acceptable manner in a sturdy extruded or die-formed frame to provide adequate support for glass. Permanent mark showing grade of glass shall be visible and glass shall be a minimum of 1/8 inch thick.
- c. Other than emergency exits designated to comply with FMVSS No. 217, *Bus Emergency Exits and Window Retention and Release*, each side window shall provide an unobstructed opening at least 9 inches high (but not more than 13 inches high) and at least 22 inches wide, obtained by lowering the window. One window on each side of the bus may be less than 22 inches wide. Movable window shall be controlled by approved lock having finger-touch opener providing for ease of operation and shall have no sharp projections. Window latches must be replaceable or rebuildable without disassembling the complete window frame or removing the window from the body. In addition, individual window latches or repair parts must be available and part numbers included in the required body parts catalog. Window seals and visors or drip molding shall be installed and unit shall provide ample protection from leakage in hardest rain.
- d. For ventilation purposes, the driver's window shall be adjustable and shall be equipped with a positive latch that can be secured from the inside of bus.
- e. There shall be installed in rear door 2 windows, 1 upper and 1 lower, set in rubber in a waterproof manner. The use of adhesives in place of the required rubber may be approved at the discretion of the Department. Total glass area in emergency door shall be a minimum of 750 square inches. Glass shall be same type as for side windows.
- f. Rear side windows located at each side of emergency door shall be set in rubber in waterproof manner. The use of adhesives in place of the required rubber may be approved at the discretion of the Department. Glass area shall be large enough to provide desirable vision to rear and shall be of same quality and grade as for side windows.
- g. Galvanized steel or aluminum, designed to near equal stiffness, as determined by inspection to give adequate support to glass, shall be used for window frames.
- h. Districts may use Lexan™ or equivalent in locations other than the windshield when replacing OEM glass, except where prohibited by FMVSS.

41. WINDSHIELD

Front body section in area of windshield shall provide for corner vision and be fitted with curved glass, 2, 3, or 4-piece flat glass as approved by the Department of Education. Glass shall be laminated safety polished plate with dark tint at top, set in rubber, waterproof, and slanted to reduce glare. The use of adhesives in place of the required rubber may be approved at the discretion of the Department. Glass shall meet current SAE specifications and Federal Motor Vehicle Safety Standards. Light tint may be used in Modified Forward Control Type B and all Type D buses in lieu of dark tint at top.

42. WINDSHIELD STEPS AND HANDLES

A step and appropriate grab handle shall be installed on each front corner of body to facilitate cleaning of windshield. The handle shall be stainless steel, chrome plated, or non-ferrous metal or may be made of non-metallic material of sufficient structural and mounting strength and resistant to weathering and deterioration and shall provide for secure mounting and adequate hand hold. Handle shall be contoured and formed to provide a comfortable and safe grip.

NOTE: Steps and handles are not required on Type A1 buses.

43. WINDSHIELD WIPERS AND WASHERS

- a. Electrical windshield wipers shall be standard on all buses. All wipers by design and installation shall provide desirable vision for drivers. Heavy-duty motor(s) shall be provided and equipped with blades of sufficient length and heavy-duty arms to clear windshield glass in driver's direct view. One switch shall control both wipers, and the switch shall be located within easy reach from driver's seat, preferably on the turn signal stalk. The system shall incorporate a variable delay wipe feature to allow drivers to adjust the speed and frequency of the wipers. Wiper system shall be designed to move blades away from driver's direct view when in the "stop" position.
- b. Windshield washers shall be electrically operated. The washer reservoir shall be made of hard plastic or other approved material and have a capacity of at least 1/2 gallon. Flexible plastic bags are not acceptable.

NOTE: Manufacturer's standard windshield wipers are acceptable on Type A1 buses.

WIRING

See **ELECTRICAL EQUIPMENT AND WIRING, page III-5.**

TYPE B MODIFIED FORWARD CONTROL, AND TYPE D FRONT ENGINE BODY EXCEPTIONS

1. The distance between barrier at rear of entrance step well and engine cover shall be a minimum of 13 inches.
2. A step, in lieu of stirrup steps, is permitted in or on the front bumper, both sides.
3. Engine cover shall be made of metal or an approved equal and shall provide adequate seal to the bus floor area to keep engine fumes from entering the passenger compartment and shall be insulated to retard transfer of heat and engine noise. Engine cover shall be hinged and equipped with a prop rod or other device so that it can be held securely in the fully open position to allow access to the engine.

TYPE D REAR ENGINE BODY EXCEPTIONS

1. Engine compartment shall be constructed to permit servicing of engine, having 1 or 2 doors opening at rear and louvered, removable panels on each side of engine compartment. Engine compartment must be sealed at top and front to retard heat transfer and prevent engine fumes from entering passenger compartment. Provisions shall be made for easy removal of engine through rear compartment.
2. Mud flaps shall be installed at rear of dual wheels.
3. Engine air intake, meeting chassis manufacturer's approval, shall be installed in approved manner to outside of body.
4. A step, in lieu of stirrup steps, is permitted in or on the front bumper, both sides.
5. Front end construction of body shall be designed to prevent distortion and vibration. Forward outer panel shall be substantial for mounting headlamps and turn signals. Provisions shall be made for servicing steering gear.
6. Bus body shall have an emergency door located on left side of bus body, hinged in front, supplemented by a rear emergency window over motor, hinged at top. There shall be an open access of at least 12 inches in width from the center aisle to the side emergency door. There shall also be attached to the door, in such a way that it is visible inside and outside the bus, labeling as follows: "This door is equipped with a hold-open device. To release, open the door to its fully opened position." This sticker shall be red on a white background and lettering shall be a minimum of ½ inch. A flip seat meeting FMVSS 222 is acceptable. Any flip seat must be free of sharp projections on the underside of the seat bottom. The underside of flip-up seat bottom must be padded and covered to remove the possibility of injury during use. Emergency door and windows shall meet FMVSS 217. Emergency window over engine compartment shall be a minimum of 16 inch x 54 inch. This window must be capable of being unlatched and opened to the hold open position by an elementary age student. Emergency Exit Windows and Roof Hatches shall meet the same requirements listed previously for all other buses under **"EMERGENCY EXITS, page III-12."**
7. Rub rails may terminate at the engine compartment.
8. Exhaust system tailpipe must exit behind the rear axle and to the rear of the passenger compartment, but does not have to exit under or behind the rear bumper.
9. Type D Rear Engine buses are exempted from the requirement for an additional electrical compartment for air conditioner circuitry provided the air conditioner control boards are installed in the rear package shelf area in a covered box.
10. There shall be an engine access panel underneath the rear seat of all rear engine buses designed to provide access to the engine.

SPECIFICATIONS FOR OPTIONAL BODY EQUIPMENT TYPE A1, A2, B, C, AND D BUSES

1. **BAGGAGE COMPARTMENTS**

Option on all bodies when available. This body option shall include a lock and be keyed-alike with any other body option requiring use of a key.

2. **DIESEL NOISE REDUCTION PACKAGE**

Option for a diesel noise reduction package, which shall include full insulation of ceiling, walls, and front and rear of bus (including body bows), plus minimum ½ inch pressure treated plywood covering the floor. Plywood shall be all-veneer APA rated sheathing marked "EXP1" or "EXT". Preservative treatment shall be a minimum of 0.40 pounds of chromated copper arsenate per cubic foot of plywood. Insulation material must be fire resistant and of a type that will not harbor dampness, and must be approved by Underwriters Laboratories, Inc. For all front engine units, this package must include full width perforated interior ceiling panels to deaden engine noise, extending from the front header panel to at least the first passenger seating position. For rear engine units, this package shall include sound deadening insulation between the engine compartment and the passenger compartment and full width perforated interior ceiling panels extending from the rear header panel forward to at least the front of the engine compartment. There shall be an additional option for perforated sound deadening panels covering the full length of the bus,

3. **FLIP-UP SEAT**

Option for a flip-up type seat in the first passenger seating position behind the driver.

4. **EXTERIOR LIGHT MONITOR**

A system of monitoring exterior lights on the front and rear of the bus from the driver's seated position is approved as an option. Such systems shall include:

- a. Pupil Warning Lamps, both **RED and AMBER**, front and rear.
- b. Tail Lamps
- c. Backup Lamps
- d. Rear Turn Signal Lamps
- e. Stop Lamps

A system that monitors only electrical circuits and does not indicate whether the bulb is operational is not acceptable. See **PUBLICATIONS, page III-17** for parts manual requirement for optional components.

5. **STRAIGHT FLOOR/ FLAT FLOOR**

- a. Option on any size bus when available for an unobstructed straight floor design (i.e., no wheel wells and no step-up at the rear of the driver's compartment). Minimum headroom of any bus equipped with this option shall remain 72 inches as per standard body specifications.
- b. Option on any size bus, when available, for an unobstructed flat floor design in the passenger compartment. If this option utilizes a raised floor that is stepped up behind the driver's area, forward edge of aisle shall have a white stripe and be labeled "Step Up" as viewed upon entering aisle and a "Step Down" label shall be visible upon exiting aisle. Minimum headroom of any bus equipped with this option shall remain 72 inches as per standard body specifications. The bus shall be equipped with 39 inch seats except for locations where lift bus specifications require a 30 inch aisle.

6. **FUEL SUPPLY LOCK**

A lock with 2 keys may be installed in the fuel supply service door of the body skirt. This body option shall be keyed alike, with any other body option requiring use of a key.

7. **REAR HEATER**

Option for an additional heater mounted to provide heat in the rear of the body. This option shall be installed under a passenger seat or shall be otherwise protected to eliminate damage to the unit and injury to the students. Shall have a minimum 80,000 BTU rating for Type B, C, and D buses. Type A buses shall have a minimum 50,000 BTU rating.

8. **BUS LOCKUP SYSTEM**

Optional whereby a bus can be locked at emergency as well as entrance door. Ignition interlock required for emergency door to prevent starting bus if emergency door is locked. This body option shall be keyed alike with any other body option requiring use of a key.

9. **PUBLIC ADDRESS SYSTEM (P.A.), RADIO**

Option for a public address system/AM/FM stereo radio with 4 speakers inside the bus and 1 heavy-duty weatherproof P.A. type speaker outside the bus with controls to permit the driver to select inside or outside speakers, mounted in the driver's compartment so that all controls are readily accessible to the driver from the normal seated position. Interior speakers shall be flush mounted. Outside speaker shall be mounted under the hood or in another protected location at the front of the bus. See **PUBLICATIONS, page III-17** for parts manual requirements for optional components. AM/FM stereo radio with 4 speakers may be offered separately. Internally mounted speakers must not be located in the driver's area.

10. **RED LIGHT ABOVE EMERGENCY DOOR**

Option for a small red light to be mounted above the emergency door on the interior of the bus that is activated when the clearance lights are on.

11. **POWDER-COATED WINDOW FRAMES**

Option for electrostatically powder-coated window frames on all types of buses to reduce friction and improve ease of operation of passenger side windows.

12. **HIGH HEADROOM BODIES**

Option for bus bodies with nominal 77 inch headroom.

13. **TAILPIPE THROUGH BUMPER**

Option, when available, for a tailpipe through the bumper, in lieu of the standard tailpipe. This tailpipe shall not require a turndown, and shall extend at least to exterior surface of rear bumper, but no more than 2 inches beyond it.

14. **TRACK SEATING**

- a. Option for a track mounted seating system using button type (L track) track, and a wheelchair securement system meeting Florida Specifications, but mounting into the track-seating track. The overhead track for shoulder harness attachment shall extend the full length of the passenger compartment on both sides. The bus shall be equipped with 39-inch seats except when lift bus specifications require a 30-inch aisle. All floor tracking shall be anodized aluminum or other material of equal strength that will resist corrosion in Florida's environment.
- b. This option shall include additional options as follows:
 - (1) Purchase of individual track seating seats.
 - (2) Delete a seat, add a wheelchair position with wheelchair tie-downs.
 - (3) Delete a wheelchair position (tie-downs), and add a standard seat.

15. **MOTION MASTERS DRIVER’S SEAT DAMPENING SYSTEM**

Option to add the Motion Master dampening system to any suspension type driver’s seat when available.

16. **INFANT SEATING**

Option for passenger seating designed to safely transport newborns, infants, or toddlers and meeting all applicable Federal Motor Vehicle Safety Standards as follows:

- a. C.E. White Child Restraint Seat.
- b. Other systems as approved by the Department of Education.

17. **POWERED ROOF VENTS**

Option for powered roof vent incorporated into each emergency roof exit/vent. These vents shall flow at least 650 cfm of air and be designed such that rain will not leak in at any time. This option shall also include an additional 6 inch fan mounted in the windshield area, operated by a separate switch.

18. **SCHOOL BUS LOCATION AND TRACKING SYSTEM**

Option for system that will use the Global Positioning System (GPS) to wirelessly report the real-time location of the bus to transportation administration. The system may also include systems that will identify individual students and report the locations and times they boarded and disembarked the bus.

19. **3-POINT SEAT BELTS AND 3-POINT SEAT BELT SEATS**

Option for 3-point seat belts in 2 and 3 passenger 3-point seat belt seats, as approved by the Department of Education.

20. **SILICONE HEATER HOSES**

Option for heater hoses constructed of silicone rubber and using shoe type clamps.

21. **DRIVER’S SEAT WITH INTEGRATED SEAT BELT**

Option for a driver’s seat meeting the requirements of **DRIVER'S SEAT AND SEAT BELT** in this section, and having a seat belt integrated into the seat back.

22. **STEERING WHEEL MOUNTED CONTROLS**

Option for steering wheel mounted entrance door and pupil warning light control switches.

23. **ZONAR PRE/POST TRIP DOCUMENTATION SYSTEM**

Option for the Zonar pre/post trip inspection system with sleeping child alert system, where available.

24. **COMPASS**

Option for a compass located in the driver’s area and visible to the driver while driving the bus.

25. **BATTERY DISCONNECT SWITCH LABELING**

Option for a label to be placed on the exterior of the bus on the cover of the compartment housing the battery disconnect switch. The label background shall be white with red one-inch letters with the wording “MAIN BATTERY DISCONNECT.”

26. **ELECTRIC POWERED DOOR FOR TYPE A**

Option for an electric powered entrance door, where available, on Type A school buses only.

